# LED

MoL

Date:	
In hands date of project:	
Project name/Number:	
Name of distributor:	
Client #:	
Name of end user:	

### **ORDERING INFORMATION**

Order code:	64809
Description:	LED/OMNI/S3/5.5W/27K/STD
UPC:	69549648098
Case quantity:	60

#### **PERFORMANCE DATA**

Shape:	OMNI
Base:	E26
Wattage (W):	5.5
Lamp voltage (VAC):	120
Colour temperature (K)**:	2 700
Average life (L70 hours):	25 000
Initial lumens (lm)*:	455
Initial lumens per watt (lm/W):	83
CRI:	81
Beam angle:	270
Power factor:	0.85
Operating temperature range:	-20 °C / - 4 °F to 40 °C / 104 °F

\*Initial lumens range: +/- 10 %

\*\*Typical colour temperature range: +/- 5 % 

WARRANTY



## CAUTIONS

NO

- Turn power off before inspection, installation, or removal.
  Risk of electrical shock do not use where directly exposed to water or weather.
  Not for use in totally enclosed luminaires.
  Suitable for use in damp locations.
  Do not open no user serviceable parts inside.
  Added weight of the device may cause instability of a freestanding portable luminaire. Use in portable table lamps in which the distance from the bottom of the base to the top of the lamp holder does not exceed three (3) times the minimum base diameter.
  Use only on 120 VAC, 60Hz circuits.
  This device is not intended for use with emergency exit fixtures or emergency exit lights.
  Compatible with most dimmers.
  For complete dimmer and warranty information visit www.standardpro.com.
  Not recommended for use with timers.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name:		
Company:		
Signature:		Da
Data is based upon tests performed in a controlled or	avironment and representative of relative performance	



MOL: 3 1/8 in. (99 mm)

Dia.: 2 3/16 in. (55 mm)

Diameter

## **DIMMER COMPATIBILITY LIST**

Legrand	HCL453P
Cooper	9531AW, AAL06P, DAL06P, SLC03P
Leviton	6674, DSL06-1LZ, DSM10-1LZ, IPL06
Lutron	AYCL-253P, CTCL-153P, DVCL-153P, DVCL-253P, DVELV-300P, NTELV-600, SELV-300P

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

**ST**ANDARD®