



# S9597

9A19/LED/5000K/120V/4PK  
9 watt; A19 LED; Frosted; 5000K Medium base; 200' beam spread; 120 volts; Non-Dimmable; 4-Pack

## Features

- Solid State LED lighting
- A-Shaped replacement lamp
- Long life
- Approved for enclosed fixtures
- Non-Dimmable



S9597

| Item Number                 | UPC             | Input Voltage                                                     | Watts         | Incandescent Equivalent | Base           | ANSI Base           | Lamp Code               |                  |
|-----------------------------|-----------------|-------------------------------------------------------------------|---------------|-------------------------|----------------|---------------------|-------------------------|------------------|
| S9597                       | 045923095979    | 120                                                               | 9             | 60W                     | Medium         | E26                 | 9A19/LED/5000K/120V/4PK |                  |
|                             |                 |                                                                   |               |                         |                |                     |                         |                  |
| Dimmable/Non-Dimmable       |                 | Finish                                                            | MOL In Inches | MOD In Inches           | Initial Lumens | Average Rated Hours | Kelvin Temp             | Color            |
| Non-Dimmable                |                 | Frost                                                             | 4-3/16"       | 2-3/8"                  | 800            | 10000               | 5000                    | Natural Light    |
|                             |                 |                                                                   |               |                         |                |                     |                         |                  |
| CRI                         | Beam Spread Deg | Operating Temperature                                             |               | Pack                    | Package Type   | RoHS Compliant      | Fixture Type            | UL or ETL Listed |
| 80                          | 200             | Operating temperature: -20°C (-4°F) to a maximum of +45°C (113°F) |               | 4                       | 4Pk            | Yes                 | Enclosed Rated          | Yes              |
| UL Classification           |                 |                                                                   |               |                         |                |                     |                         |                  |
| cULus - Damp Location Rated |                 |                                                                   |               |                         |                |                     |                         |                  |



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
www.satco.com

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

