



LED Filament Long Life lamps offer the best of both worlds. They bring style and life to any decor while offering an exceptional long life of 25 000 hours. Make your luminaires stand out with STANDARD's wide variety of shapes and filaments. Adding an LED Filament lamp to your decor is a small touch that will make a big difference.



Order Code	Description	Filament type	Watts (W)	Base	Volts (V)	Colour temp. (K)	Finish	CRI	Average life (hrs)	Initial lumens ¹ (lm)	Incan equivalent (W)	Case qty
A19												
MOL: 4 11/32 in. (110 mm) Dia: 2 3/8 in. (60 mm)												
64526	LED/A19/6W/27K/LL/Z/FIL/STD	Zig-Zag	6	E26	120	2 700	Clear	80	25 000	600	60	50/100
ST19												
MOL: 5 1/8 in. (130 mm) Dia: 2 9/32 in. (58 mm)												
64530	LED/ST19/6W/27K/LL/S/FIL/STD	Spiral	6	E26	120	2 700	Clear	80	25 000	600	40	50/100
T14												
MOL: 4 29/32 in. (125 mm) Dia: 1 25/32 in. (45 mm)												
64528	LED/T14/6W/27K/LL/S/FIL/STD	Spiral	6	E26	120	2 700	Clear	80	25 000	600	40	50/100
T10												
MOL: 8 27/32 (225 mm) Dia: 1 3/16 in. (30 mm)												
64518	LED/T10/3W/27K/LL/V/FIL/STD	Vertical	3	E26	120	2 700	Clear	80	25 000	300	40	50/100
64520	LED/T10/6W/27K/LL/V/FIL/STD	Vertical	6	E26	120	2 700	Clear	80	25 000	600	60	50/100
64522	LED/T10/6W/27K/LL/Z/FIL/STD	Zig-Zag	6	E26	120	2 700	Clear	80	25 000	600	60	50/100
T10L												
MOL: 11 13/16 in. (300 mm) Dia: 1 3/16 in. (30 mm)												
64524	LED/T10L/6W/27K/LL/Z/FIL/STD	Zig-Zag	6	E26	120	2 700	Clear	80	25 000	600	40	50/100



¹ Typical lumens +/- 5%
² For a complete list of compatible dimmers, please visit www.standardpro.com

LED Filament – Long Life



A19



ST19



T14



T10



T10L

Order Code	Description	Filament type	Watts (W)	Base	Volts (V)	Colour temp. (K)	Finish	CRI	Average life (hrs)	Initial lumens ¹ (lm)	Incan equivalent (W)	Case qty
A19												
MOL: 4 11/32 in. (110 mm) Dia: 2 3/8 in. (60 mm)												
64527	LED/A19/6W/22K/LL/A/Z/FIL/STD	Zig-Zag	6	E26	120	2 200	Amber	95	25 000	450	60	50/100
ST19												
MOL: 5 1/8 in. (130 mm) Dia: 2 9/32 in. (58 mm)												
64531	LED/ST19/6W/22K/LL/A/S/FIL/STD	Spiral	6	E26	120	2 200	Amber	95	25 000	450	40	50/100
T14												
MOL: 4 29/32 in. (125 mm) Dia: 1 25/32 in. (45 mm)												
64529	LED/T14/6W/22K/LL/A/S/FIL/STD	Spiral	6	E26	120	2 200	Amber	95	25 000	450	40	50/100
T10												
MOL: 8 27/32 (225 mm) Dia: 1 3/16 in. (30 mm)												
64519	LED/T10/3W/22K/LL/A/V/FIL/STD	Vertical	3	E26	120	2 200	Amber	95	25 000	250	40	50/100
64521	LED/T10/6W/22K/LL/A/V/FIL/STD	Vertical	6	E26	120	2 200	Amber	95	25 000	450	60	50/100
64523	LED/T10/6W/22K/LL/A/Z/FIL/STD	Zig-Zag	6	E26	120	2 200	Amber	95	25 000	450	60	50/100
T10L												
MOL: 11 13/16 in. (300 mm) Dia: 1 3/16 in. (30 mm)												
64525	LED/T10L/6W/22K/LL/A/Z/FIL/STD	Zig-Zag	6	E26	120	2 200	Amber	95	25 000	450	40	50/100

¹ Typical lumens +/- 5%

² For a complete list of compatible dimmers, please visit www.standardpro.com



INDOOR



DIMMABLE



DAMP



BEAM
SPREAD



WARRANTY



COMPLIANT



NO
MERCURY



FCC



UL US

LED Filament Victorian Style – Long Life