

TECHNICAL DATA SHEET

CLEAR VINYL TUBE (JFT)

Applications: It is clear, flexible, easy to clean, abrasion resistant and non-contaminating.

It is suitable for the conveyance of air, and water and is used extensively where food and beverages are conveyed.



Clear polyvinyl-chloride tube is manufactured from F.D.A. approved resins.



CERTIFIED UNDER STANDARD 51 and 61

NOTE

THE WORKING PRESSURES LISTED FOR THE VINYL TUBE IS RATED AT +70°F, +21°C. ANY AMBIENT OR INTERNAL INCREASE IN TEMPERATURE WILL LOWER THE ABOVE LISTED WORKING PRESSURES. THIS TUBE IS NOT RECOMMENDED FOR MILK CONTACT, ALCOHOL (LIQUOR) OR MEDICAL APPLICATIONS.

- **PACKAGING:** 100 FT COILS 1/8" TO 1-1/4" I.D.
500 FT REELS 1/8" TO 1/2" I.D.
300 FT REELS 5/8" TO 1" I.D.
50 FT COIL 1-1/2" I.D.

NOTE: TO ORDER REEL LENGTHS CHANGE -100 TO -REEL

- **TEMPERATURE:** +25°F TO +149°F, -4°C TO +65°C
- **FITTINGS:** HOSE BARBS PAGE 62 - 64
- * **THESE ITEMS ARE ONLY AVAILABLE IN 100 FT COILS.**

Dash Size	Tube O.D. (IN.)	Actual I.D. (IN.)	Working Pressure (P.S.I.)
-42	1/4	1/8	65
-53	5/16	3/16	55
-63	3/8	3/16	65
-64	3/8	1/4	55
-74	7/16	1/4	60
-75	7/16	5/16	50
-84	1/2	1/4	70
-85	1/2	5/16	60
-86	1/2	3/8	45
-106	5/8	3/8	55
-108	5/8	1/2	30
-128	3/4	1/2	45
-1210	3/4	5/8	30
-1410	7/8	5/8	40
-1612	1	3/4	35
-1812	1-1/8	3/4	50
-2014	1-1/4	7/8	35
-2016	1-1/4	1	25
-2416	1-1/2	1	35
-2420	1-1/2	1-1/4	20
-3224	2	1-1/2	35