

Version 1.2	Revision Date: 02/10/2015	MSDS Numbe 31814-00003	r: Date of last issue: 12/16/2014 Date of first issue: 11/24/2014			
SECTION	SECTION 1. PRODUCT AND COMPANY IDENTIFICATION					
Proc	luct name	: PURELL®	Advanced Moisturizing Foam Hand Rub			
Man	ufacturer or supplier's	details				
Com	pany name of supplier	: GOJO Inde	ustries, Inc.			
Addı	ress	: One GOJO Akron OH	) Plaza, Suite 500 44311			
Tele	phone	: 1 (330) 25	5-6000			
Eme	ergency telephone	: 1-800-424	9300 CHEMTREC			
Rec	ommended use of the o	chemical and re	strictions on use			
Reco	ommended use	: Hand Sani	tizer			
Rest	trictions on use	consumers foreseeabl specifically exempt fro While this contains va proper use as well as spills. This employees intended-u	ersonal care or cosmetic product that is safe for s and other users under normal and reasonably e use. Cosmetics and consumer products, defined by regulations around the world, are m the requirement of an SDS for the consumer. material is not considered hazardous, this SDS aluable information critical to the safe handling and of the product for industrial workplace conditions unusual and unintended exposures such as large SDS should be retained and available for and other users of this product. For specific se guidance, please refer to the information n the package or instruction sheet.			

#### SECTION 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

WARNING				
Appearance	liquid			
Color	clear, Colorless to pale yellow			
Odor	alcohol-like			
Hazard Summary	Flammable liquid and vapor. Irritant Specific Target Organ Toxicity			
WHMIS Regulatory status	: This product, material or substance is a WHMIS controlled			



Vers 1.2	sion	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014				
		<b>ial Health Effects</b> Organs	: Central nervous system					
	Inhalat	Ū		: May cause drowsiness or dizziness.				
	Skin		: No significant irrit exposure.	: No significant irritation expected from a single short-term exposure.				
	Eyes		: Causes eye irrita	: Causes eye irritation.				
	Ingestion		: No significant effects expected from a single short-term exposure.					
	Aggravated Medical Condition		: None known.					
	Carcin	ogenicity:						
	IARC		No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.					
	ACGI	1	Confirmed animal ca mans	arcinogen with unknown relevance t	o hu-			
			Ethanol		64-17-5			

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 50 - < 70
Propan-2-ol	67-63-0	>= 1 - < 5

#### SECTION 4. FIRST AID MEASURES

General advice	<ul> <li>In the case of accident or if you feel unwell, seek medical advice immediately.</li> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> </ul>
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Get medical attention if symptoms occur.



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014		
In case of eye contact		<ul> <li>In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.</li> <li>If easy to do, remove contact lens, if worn.</li> <li>Get medical attention.</li> </ul>			
If swallowed		: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.			
Protection of first-aiders		and use the reco	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.		
Not	es to physician	: Treat symptoma	tically and supportively.		

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Dry chemical Carbon dioxide (CO2)
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire fighting	:	Do not use a solid water stream as it may scatter and spread fire. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Exposure to combustion products may be a hazard to health.
Hazardous combustion prod- ucts	:	Carbon oxides Silicon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Remove all sources of ignition.
protective equipment and	Use personal protective equipment.
emergency procedures	Follow safe handling advice and personal protective
	equipment recommendations.



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014	
Environmental precautions		<ul> <li>Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.</li> </ul>		
	ds and materials for nment and cleaning up	Soak up with ine Suppress (knock jet. For large spills, p containment to k can be pumped, container. Clean up remain absorbent. Local or national disposal of this m employed in the determine which Sections 13 and	Is should be used. t absorbent material. down) gases/vapors/mists with a water spray provide diking or other appropriate eep material from spreading. If diked material store recovered material in appropriate Ing materials from spill with suitable regulations may apply to releases and naterial, as well as those materials and items cleanup of releases. You will need to regulations are applicable. 15 of this SDS provide information regarding ational requirements.	

#### SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation.
Advice on safe handling	:	Do not get on skin or clothing. Do not breathe vapors or spray mist. Do not swallow. Do not get in eyes. Handle in accordance with good industrial hygiene and safety practice. Non-sparking tools should be used. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Keep in properly labeled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.



Version	Revision Date:	MSDS Number:	Date of last issue: 12/16/2014
1.2	02/10/2015	31814-00003	Date of first issue: 11/24/2014
Mater	ials to avoid	Strong oxidizing Organic peroxid Flammable solid Pyrophoric liquid Pyrophoric solid Self-heating sub	les ds ds ds ostances and mixtures d mixtures which in contact with water emit

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,880 mg/m3	CA AB OEL
		STEL	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,880 mg/m3	CA QC OEL
		STEL	1,000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm 492 mg/m3	CA AB OEL
		STEL	400 ppm 984 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		STEL	400 ppm	CA BC OEL
		TWAEV	400 ppm 983 mg/m3	CA QC OEL
		STEV	500 ppm 1,230 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
Glycerine	56-81-5	TWA	10 mg/m3	CA BC OEL
		TWA (Respirable)	3 mg/m3	CA BC OEL
		TWA (Mist)	10 mg/m3	CA BC OEL
		TWA (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Respirable mist)	3 mg/m3	CA BC OEL

#### Ingredients with workplace control parameters

Revision Date:

Version



Date of last issue: 12/16/2014

### PURELL® Advanced Moisturizing Foam Hand Rub

MSDS Number:

sion	Revision Date: 02/10/2015		5 Number: -00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014			
Biolo	gical occupational	exposure	limits				
Ingrea	<u> </u>	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentratio n	Basis
Propa	an-2-ol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIF BEI
Engineering measures :		Us ve	nimize workpla se only in an ar ntilation. se with local ext	ea equipped	with explos		aust
Perso	onal protective equ	ipment					
Respi	iratory protection	ve	e respiratory p ntilation is prov at exposures ar	vided or expo	sure asses	sment demon	strates
Filt	er type	: Co	mbined particu	ulates and or	ganic vapo	r type	
	protection terial	: Im	pervious glove	s			
Ma	terial	: Fla	ame retardant g	gloves			
Rei	marks	on tim Fc glo	noose gloves to the concentrat ne is not detern or special applic sistance to che oves with the gl eaks and at the	tion specific the nined for the cations, we re micals of the love manufactor	o place of product. C commend aforement cturer. Was	work. Breakthr hange gloves clarifying the ioned protectiv	rough often! ve
Eye p	protection		ear the followin fety goggles	g personal p	rotective e	quipment:	
Skin a	and body protection	re: po W Fla Sk	elect appropriat sistance data a tential. ear the followin ame retardant a in contact mus othing (gloves, a	nd an asses g personal p antistatic prot t be avoided	sment of th rotective entective cloth by using ir	e local exposu quipment: ning.	ire
Hygie	loca Wh		sure that eye f cated close to the hen using do na ash contaminat	he working p ot eat, drink	lace. or smoke.		are



Version 1.2	Revision Date: 02/10/2015		DS Number: 14-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014
SECTION	I 9. PHYSICAL AND CHI	EMIC		S
Арре	earance	:	liquid	
Colo	r	:	clear, Colorless t	o pale yellow
Odoi	r	:	alcohol-like	
Odoi	r Threshold	:	No data available	9
pН		:	6 - 9	
Melti	ing point/freezing point	:	No data available	9
Initia rang	l boiling point and boiling e	:	73.00 °C	
Flash	h point	:	26.00 °C	
Evap	poration rate	:	No data available	9
Flam	nmability (solid, gas)	:	Not applicable	
Uppe	er explosion limit	:	No data available	9
Lowe	er explosion limit	:	No data available	9
Vapo	or pressure	:	No data available	9
Rela	tive vapor density	:	No data available	9
Dens	sity	:	0.0881 g/cm3	
	bility(ies) ′ater solubility	:	soluble	
	tion coefficient: n- nol/water	:	Not applicable	
Auto	ignition temperature	:	No data available	9
Deco	omposition temperature	:	The substance o	r mixture is not classified self-reactive.
Visco Vi	osity scosity, kinematic	:	10 - 20 mm2/s (2	20 °C)
Expl	osive properties	:	Not explosive	
Oxid	izing properties	:	The substance o	r mixture is not classified as oxidizing.

#### SECTION 10. STABILITY AND REACTIVITY



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014
Re	activity	: Not classified a	s a reactivity hazard.
Ch	emical stability	: Stable under no	ormal conditions.
Pos tior	ssibility of hazardous reacons NS	Vapors may for	id and vapor. m explosive mixture with air. strong oxidizing agents.
Co	nditions to avoid	: Heat, flames a	nd sparks.
Inc	ompatible materials	: Oxidizing agen	ts
	zardous decomposition ducts	: No hazardous	decomposition products are known.

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

Ingredients:	
Ethanol:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 124.7 mg/l Exposure time: 4 h Test atmosphere: vapor
Propan-2-ol: Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 72.6 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	: LD50 (Rat): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

### Product:

Result: No skin irritation

#### Ingredients:

Ethanol: Species: Rabbit Method: OECD Test Guideline 404 Result: No skin irritation

Propan-2-ol: Species: Rabbit Result: No skin irritation



Version	<b>Revision Date:</b>
1.2	02/10/2015

MSDS Number: 31814-00003

Date of last issue: 12/16/2014 Date of first issue: 11/24/2014

#### Serious eye damage/eye irritation

Causes eye irritation.

#### Ingredients:

**Ethanol:** Species: Rabbit Result: Irritation to eyes, reversing within 21 days Method: OECD Test Guideline 405

#### Propan-2-ol:

Species: Rabbit Result: Irritation to eyes, reversing within 21 days

#### Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitization.

#### Ingredients:

#### Ethanol:

Test Type: Local lymph node assay (LLNA) Routes of exposure: Skin contact Species: Mouse Result: negative

#### Propan-2-ol:

Test Type: Buehler Test Routes of exposure: Skin contact Species: Guinea pig Method: OECD Test Guideline 406 Result: negative

#### Germ cell mutagenicity

Not classified based on available information.

#### Ingredients:

Ethanol: Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: negative
Propan-2-ol:	
Genotoxicity in vitro	<ul> <li>Test Type: Bacterial reverse mutation assay (AMES) Result: negative</li> </ul>



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014
Geno	toxicity in vivo	cytogenetic Species: Mo	use Route: Intraperitoneal injection
	n <b>ogenicity</b> lassified based on ava	ailable information.	
Propa Speci Applic Expos Metho Resul	dients: an-2-ol: ies: Rat cation Route: inhalatic sure time: 104 weeks od: OECD Test Guide It: negative oductive toxicity	line 451	
	lassified based on ava	ailable information.	
<u>Ingre</u> Ethar	<u>dients:</u> nol:		
	ts on fertility	Species: Mo Application I	Route: Ingestion CD Test Guideline 416
Propa	an-2-ol:		
	ts on fertility	Species: Ra	Route: Ingestion
Effect	ts on fetal developme	Species: Ra	Route: Ingestion
STOT	ſ-single exposure		
	-term exposure may c	ause target organ e	ffects

#### Ingredients:

**Propan-2-ol:** Assessment: May cause drowsiness or dizziness.

#### STOT-repeated exposure

Not classified based on available information.



Version	Revision Date:	MSDS Number:	Dat
1.2	02/10/2015	31814-00003	Dat

Date of last issue: 12/16/2014 Date of first issue: 11/24/2014

#### Repeated dose toxicity

#### Ingredients:

Ethanol: Species: Rat NOAEL: 2,400 mg/kg Application Route: Ingestion Exposure time: 2 y

#### Propan-2-ol:

Species: Rat NOAEL: 5000 ppm Application Route: inhalation (vapor) Exposure time: 104 w Method: OECD Test Guideline 413

#### Aspiration toxicity

Not classified based on available information.

#### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Ingredients:		
Ethanol: Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 9 d
Toxicity to bacteria	:	EC50 (Photobacterium phosphoreum): 32.1 mg/l Exposure time: 0.25 h
<b>Propan-2-ol:</b> Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to algae	:	ErC50 (Scenedesmus quadricauda (Green algae)): > 1,800 mg/l Exposure time: 8 d



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014
Toxic	ity to bacteria	: EC50 (Pseudor Exposure time:	monas putida): > 1,050 mg/l 16 h
Persi	stence and degrada	bility	
Ethai	e <mark>dients:</mark> nol: egradability	: Result: Readily Biodegradation Exposure time:	: 84 %
	<b>an-2-ol:</b> egradability	: Result: rapidly	degradable
Bioa	ccumulative potentia	al	
<b>Etha</b> ı Partit	dients: nol: ion coefficient: n- iol/water	: log Pow: -0.35	
Partit	<b>an-2-ol:</b> ion coefficient: n- iol/water	: log Pow: 0.05	
Mobi	lity in soil		
No da	ata available		
••	r adverse effects ata available		

Disposal methods		
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum.

#### SECTION 14. TRANSPORT INFORMATION

#### International Regulation

UNRTDG	
UN number	: UN 1987
Proper shipping name	: ALCOHOLS, N.O.S.



Version 1.2	Revision Date: 02/10/2015	MSDS Number: 31814-00003	Date of last issue: 12/16/2014 Date of first issue: 11/24/2014
Class Packing group Labels		(Ethanol, Prop : 3 : III : 3	pan-2-ol)
Class Packir Labels Packir aircraf Packir	No. shipping name g group g instruction (cargo	<ul> <li>: UN 1987</li> <li>: Alcohols, n.o.: (Ethanol, Prop.</li> <li>: 3</li> <li>: III</li> <li>: Flammable Lie</li> <li>: 366</li> <li>: 355</li> </ul>	pan-2-ol)
Class Packir Labels EmS C Marine <b>Trans</b>	mber shipping name g group Code e pollutant	-	

#### **Domestic regulation**

TDG	
UN number	: UN 1987
Proper shipping name	: ALCOHOLS, N.O.S.
	(Ethanol, Propan-2-ol)
Class	: 3
Packing group	: 111
Labels	: 3
ERG Code	: 127
Marine pollutant	: no

#### SECTION 15. REGULATORY INFORMATION

WHMIS Classification	: B2: Flammable Liquid	
		D2B: Toxic Material Causing Other Toxic Effects

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

### The ingredients of this product are reported in the following inventories:AICS: All ingredients listed or exempt.



Version	Revision Date:	MSDS Number:	Date of last issue: 12/16/2014
1.2	02/10/2015	31814-00003	Date of first issue: 11/24/2014

#### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA)

#### SECTION 16. OTHER INFORMATION

Full text of other abbreviations						
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)				
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)				
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)				
CA BC OEL	:	Canada. British Columbia OEL				
CA QC OEL	:	Québec. Regulation respecting occupational health and safe- ty, Schedule 1, Part 1: Permissible exposure values for air- borne contaminants				
ACGIH / TWA	:	8-hour, time-weighted average				
ACGIH / STEL	:	Short-term exposure limit				
CA AB OEL / TWA	:	8-hour Occupational exposure limit				
CA AB OEL / STEL	:	15-minute occupational exposure limit				
CA BC OEL / TWA	:	8-hour time weighted average				
CA BC OEL / STEL	:	short-term exposure limit				
CA QC OEL / TWAEV	:	Time-weighted average exposure value				
CA QC OEL / STEV	:	Short-term exposure value				
Sources of key data used to compile the Material Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen- cy, http://echa.europa.eu/				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8