



Revision Number: 002.0

Issue date: 03/30/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>LePage Heavy Duty Contact Cement</b>	<b>IDH number:</b>	1504725
<b>Product type:</b>	Contact adhesive	<b>Region:</b>	Canada
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	
<b>Company address:</b>			
Henkel Canada Corporation			
2515 Meadowpine Boulevard			
Mississauga, Ontario L5N 6C3			
		Telephone: +1 (800) 624-7767	
		MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY	
		Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887	

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** HIGHLY FLAMMABLE LIQUID AND VAPOR.  
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.  
MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.  
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.
<b>Response:</b>	IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

IDH number: 1504725

Product name: LePage Heavy Duty Contact Cement

**Storage:**

lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

**Disposal:**

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Solvent naphtha (petroleum), light aliph., <0.1% benzene	64742-89-8	30 - 40
Methyl ethyl ketone	78-93-3	10 - 20
n-Heptane	142-82-5	10 - 20
Propyl acetate	109-60-4	5 - 10
Rosin, polymer with phenol	68083-03-4	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air, consult doctor if complaint persists.
<b>Skin contact:</b>	Rinse immediately with plenty of running water, seek medical advice if necessary.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Seek medical advice.
<b>Symptoms:</b>	See Section 11.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self contained breathing apparatus. Wear full protective clothing.
<b>Unusual fire or explosion hazards:</b>	None known.
<b>Hazardous combustion products:</b>	Carbon dioxide. Carbon monoxide.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Soak up with inert absorbent. Store in a closed container until ready for disposal.

## 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

**Storage:** Keep the container tightly closed and in a cool, well-ventilated place.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Solvent naphtha (petroleum), light aliph., <0.1% benzene	None	100 ppm (400 mg/m3) PEL	None	None
Methyl ethyl ketone	200 ppm TWA 300 ppm STEL	200 ppm (590 mg/m3) PEL	None	None
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Propyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (840 mg/m3) PEL	None	None
Rosin, polymer with phenol	None	None	None	None

**Engineering controls:** Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	yellow to tan
<b>Odor:</b>	Solvent
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.85
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	-9 °C (15.8 °F) no method-9 °C (15.8 °F) no method
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not available.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	77.4 %; 644.8 g/l
<b>Viscosity:</b>	1,000 - 1,400 cp
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO <sub>2</sub> ) are released.
<b>Incompatible materials:</b>	Strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Eyes, Inhalation, Skin, Ingestion

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	Vapors may cause headaches, nausea, dizziness and respiratory tract irritation.
<b>Skin contact:</b>	Irritating to skin.
<b>Eye contact:</b>	Liquid or vapors may irritate the eyes.
<b>Ingestion:</b>	Harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Solvent naphtha (petroleum), light aliph., <0.1% benzene	None	Irritant
Methyl ethyl ketone	Oral LD50 (Mouse) = 670 mg/kg Oral LD50 (Rat) = 2,300 - 3,500 mg/kg Oral LD50 (Rat) = 4,500 - 6,800 mg/kg Dermal LD50 (Rabbit) = > 8,000 mg/kg Inhalation LC50 (Rat, 4 h) = 11700 ppm	Irritant, Central nervous system
n-Heptane	Inhalation LC50 (Rat, 4 h) = 103 mg/l	Central nervous system, Irritant
Propyl acetate	Oral LD50 (Mouse) = 8,300 mg/kg Oral LD50 (Rabbit) = 6.64 g/kg Oral LD50 (Rat) = 9,370 mg/kg	Central nervous system, Irritant
Rosin, polymer with phenol	None	Allergen, Corrosive, Irritant, Respiratory, Skin

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Solvent naphtha (petroleum), light aliph., <0.1% benzene	No	No	No
Methyl ethyl ketone	No	No	No
n-Heptane	No	No	No
Propyl acetate	No	No	No
Rosin, polymer with phenol	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** ADHESIVES  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Adhesives  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** ADHESIVES  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** II  
**Marine pollutant:** Heptanes

### 15. REGULATORY INFORMATION

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

### 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 2

**Prepared by:** Donna Houston, Regulatory Affairs Specialist

**Issue date:** 03/30/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.