



Revision Number: 002.0

Issue date: 03/24/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LePage Stik 'n Seal Outdoor Adhesive	IDH number:	1716911
Product type:	Contact adhesive	Region:	Canada
Restriction of Use:	None identified	Contact information:	
Company address:			
Henkel Canada Corporation			
2515 Meadowpine Boulevard			
Mississauga, Ontario L5N 6C3			
		Telephone: +1 (800) 624-7767	
		MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY	
		Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887	

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOR.
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.
Storage:	

IDH number: 1716911

Product name: LePage Stik 'n Seal Outdoor Adhesive

Disposal:

Keep cool. Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
n-Heptane	142-82-5	20 - 30
Distillates, petroleum, heavy thermal cracked, polymd., hydrogenated	88526-47-0	10 - 20
Propyl acetate	109-60-4	10 - 20
Methylcyclohexane	108-87-2	1 - 5
Octane	111-65-9	1 - 5
Propanol-1	71-23-8	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Administer oxygen or artificial respiration as needed. If symptoms develop and persist, get medical attention.
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.
Ingestion:	Get immediate medical attention. Do not induce vomiting.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively. Aspiration may cause pulmonary edema or aspiration pneumonia.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Vapors are heavier than air and may travel along floor to an ignition source. May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:

Keep away from heat, spark and flame. Keep container closed. Keep out of the reach of children. Use only with adequate ventilation. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. Use proper bonding and/or grounding procedures.

Storage:

For safe storage, store between -18 °C (0.4 °F) and 35 °C (95°F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
n-Heptane	400 ppm TWA 500 ppm STEL	500 ppm (2,000 mg/m3) PEL	None	None
Distillates, petroleum, heavy thermal cracked, polymd., hydrogenated	None	None	None	None
Propyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (840 mg/m3) PEL	None	None
Methylcyclohexane	400 ppm TWA	500 ppm (2,000 mg/m3) PEL	None	None
Octane	300 ppm TWA	500 ppm (2,350 mg/m3) PEL	None	None
Propanol-1	100 ppm TWA	200 ppm (500 mg/m3) PEL	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear safety glasses with side shields.

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid, gel-like
Color:	Colorless
Odor:	Solvent, Sweet, Mild
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	94 °C (201.2 °F) Supplier method
Melting point/ range:	Not available.
Specific gravity:	0.86
Vapor density:	Heavier than air.
Flash point:	-10 °C (14°F) ASTM D56 22.1 TAG-4
Flammable/Explosive limits - lower:	1 %
Flammable/Explosive limits - upper:	6.5 %
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	> 1 (Butyl acetate = 1)
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available.
VOC content:	48 %; 409 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Viscosity:	13,000 - 20,000 mPa.s
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	This product may react with strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
------------------------------	------------------------

Potential Health Effects/Symptoms

Inhalation:	Vapors may cause headaches, nausea, dizziness and respiratory tract irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Prolonged exposure to solvents may cause adverse effects to the liver, urinary, and reproductive systems. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
Skin contact:	This product may cause irritation to the skin. This product may cause an allergic skin reaction.
Eye contact:	This product may cause irritation to the eyes.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
n-Heptane	Inhalation LC50 (Rat, 4 h) = 103 mg/l	Central nervous system, Irritant
Distillates, petroleum, heavy thermal cracked, polymd., hydrogenated	None	No Records
Propyl acetate	Oral LD50 (Mouse) = 8,300 mg/kg Oral LD50 (Rabbit) = 6.64 g/kg Oral LD50 (Rat) = 9,370 mg/kg	Central nervous system, Irritant
Methylcyclohexane	None	Central nervous system, Irritant, Kidney, Liver
Octane	Inhalation LC50 (Rat, 4 h) = 118 mg/l	Central nervous system, Irritant, Lung
Propanol-1	Oral LD50 (Mouse) = 6,800 mg/kg Oral LD50 (Rabbit) = 2.8 g/kg Oral LD50 (Rat) = 1.87 g/kg	Allergen, Central nervous system, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
n-Heptane	No	No	No
Distillates, petroleum, heavy thermal cracked, polymd., hydrogenated	No	No	No
Propyl acetate	No	No	No
Methylcyclohexane	No	No	No
Octane	No	No	No
Propanol-1	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name:	ADHESIVES (n-Heptane)
Hazard class or division:	3
Identification number:	UN 1133
Packing group:	II
Marine pollutant:	n-Heptane

15. REGULATORY INFORMATION**Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3

Prepared by: Donna Houston, Regulatory Affairs Specialist

Issue date: 03/24/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.