

Tag: \_

## Non-Freeze Exposed Hydrant with Vacuum Breaker

**SPECIFICATION:** Watts Drainage Products HY-420 non-freeze key operated wall hydrant with chrome plated face, integral vacuum breaker, 3/4"(19) hose connection, all bronze head, seat casting and internal working parts, galvanized wall casing and hydrant key.

**FUNCTION:** For installation in exterior walls that will be exposed to freezing temperatures, where a self draining hydrant with integral vacuum is required.

		Order (	Code: HY-420-	□-□
		Ex. HY-4	420-10-88	
		Wall T	hickness (Select One	
		Suffix	Description	
	2 13/16"	-4	4" Thick	
		-6 -8	6" Thick 8" Thick	
		-10	10" Thick	
		-12 -14	12" Thick 14" Thick	
SPECIFY		-16	16" Thick	
WALL THICKNESS		-18 -20	18" Thick 20" Thick	
		-24	24" Thick	
	)//	Other	Specify	
		Options Suffix	s (Select One or More Description	e)
4 1/4" (108)	/	-1"	1" Hose Connection	
		-88	Wall Clamp	
2.1/2"	<ul> <li>— 3/4"(19) INTERNA THREADED INLET</li> </ul>	L		
	CHROME PLATED N	ION-		
	FREEZING SELF DRA	INING		
	HYDRANT WITH IN VACUUM BREAKER	IREGRAL		
and a set of the set o				
	- 3/4"(19) OR 1"(25			
	HOSE CONNECTION VACUUM BREAKER			
4-1/2"	*LE	AD-FREE		
(114) Recommended Wall Opening:		DRANTS		
2" x 4" (51 x 102)			-	
Job Name Co	ntractor			
Job Location Cc	ntractor's P.O. No.			
Engineer Re	presentative			
Watts product specifications in U.S. customary units and metric are approximate and are provided for refer				
precise measurements, please contact Watts Technical Service. Watts reserves the right to change or moc construction, specifications, or materials without prior notice and without incurring any obligation to make modifications on Watts products previously or subsequently sold.				TS
USA: Tel: (800) 338-2581 • Fax: (828) 248-3929 • Watts.com		A Watts	Water Technologies	Company

Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • Watts.ca Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • Watts.com