

SAFETY DATA SHEET

Water Analysis Test Kit

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : Water Analysis Test Kit

Product code : 38983

Product description : Not available.

Product type : Liquid.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Material uses : Analytical reagent. 1.3 Details of the supplier of the safety data sheet

Supplier Fernox

2 Genesis Business Park

Albert Drive Sheerwater

Woking GU21 5RW

Information contact : +44 (0) 330 100 7750

+44 (0) 330 100 7751

europeanregulatory@macdermid.com

1.4 Emergency telephone number

Supplier

Telephone number : +44 (0) 330 100 7750

Hours of operation 24/7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Date of issue/Date of revision : 30.11.2016

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412 Ingredients of unknown

toxicity

Ingredients of unknown

ecotoxicity

A MacDermid Performance Solutions Business A Platform Specialty Products Company



Water Analysis Test Kit 2/19

SECTION 2: Hazards identification

Classification according to Directive 1999/45/EC [DPD]

Europe

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

: Xn; R20/21/22 Classification

> **R33** R52/53

Human health hazards : Harmful by inhalation, in contact with skin and if swallowed. Danger of cumulative

effects.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms





Signal word Warning

Hazard statements : May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Use only outdoors or in a well-ventilated area. Avoid release to the environment.

Do not breathe vapour.

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call Response

a POISON CENTER or physician if you feel unwell.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazardous ingredients : inorganic compounds of mercury

Supplemental label : Not applicable.

elements

2.3 Other hazards

Other hazards which do not result in classification : None known.



3/19 Water Analysis Test Kit

SECTION 3: Composition/information on ingredients

: Mixture Substance/mixture

Date of issue/Date of revision : 30.11.2016

			<u>Classification</u>		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Europe					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	
Austria					
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
or moreary	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Belgium					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
·	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Bulgaria inorganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury		<1		·	.,,,,,
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Croatia	50.000.450.0		T D00/07/00		[4] [0]
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
•	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Czech Republic					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
o. moroury	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	



Water Analysis Test Kit 4/19

SECTION 3: Composition/information on ingredients

Date of issue/Date of revision : 30.11.2016

Denmark					
rorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
•	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Estonia					
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
Finland	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Finland in organic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury		<1		·	
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
France	FC: 222 452 2	≥0.3 -	T + D26/27/20	Acute Tev. 2, H200	[1] [2]
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1][2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Germany					
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Greece					
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Hungary					
inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
-	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Ireland					
i e	İ	1	I	ĺ	i

5/19 Water Analysis Test Kit

SECTION 3:	Composition	/information	on ingredients
	OULIDOULIOLI	/ 11 11 OI 11 14 LIOI 1	OII IIIMI CAICIILO

Date of issue/Date of revision: 30.11.2016

inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
Italy	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
norganic compounds	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Latvia Inorganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury		<1		·	['] [-]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Lithuania					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Netherlands					.41 .01
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Norway					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Poland					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
•	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Portugal					

Water Analysis Test Kit 6/19

SECTION 3: Composition/information on ingredients

inorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
Romania	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
rorganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury Slovakia	CAS: 10045-94-0 Index: 080-002-00-6	<1	R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
inorganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury	CAS: 10045-94-0 Index: 080-002-00-6	<1	R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Slovenia					
inorganic compounds of mercury	EC: 233-152-3 CAS: 10045-94-0 Index: 080-002-00-6	≥0.3 - <1	T+; R26/27/28 R33 N; R50/53	Acute Tox. 2, H300 Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1] [2]
Spain Morganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury Sweden	CAS: 10045-94-0 Index: 080-002-00-6	<1	R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
morganic compounds	EC: 233-152-3	≥0.3 -	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
of mercury	CAS: 10045-94-0 Index: 080-002-00-6	<1	R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
Switzerland					
norganic compounds of mercury	EC: 233-152-3 CAS: 10045-94-0 Index: 080-002-00-6	≥0.3 - <1	T+; R26/27/28 R33 N; R50/53	Acute Tox. 2, H300 Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1] [2]
Turkey				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	

A MacDermid Performance Solutions Business

A Platform Specialty Products Company

Water Analysis Test Kit 7/19

SECTION 3: Composition/information on ingredients

rorganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
·	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
United Kingdom (UK)					
norganic compounds of mercury	EC: 233-152-3	≥0.3 - <1	T+; R26/27/28	Acute Tox. 2, H300	[1] [2]
·	CAS: 10045-94-0 Index: 080-002-00-6		R33 N; R50/53	Acute Tox. 1, H310 Acute Tox. 2, H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Water Analysis Test Kit 8/19

SECTION 4: First aid measures

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : May cause respiratory irritation.

: No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data. Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments**

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

No specific data.

5.3 Advice for firefighters

Special precautions for

fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Date of issue/Date of revision : 30.11.2016

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



Water Analysis Test Kit 9/19

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 30°C (41 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

10/19 Water Analysis Test Kit

SECTION 7: Handling and storage

7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

Date of issue/Date of revision : 30.11.2016

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Europe	
rorganic compounds of mercury	EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values TWA: 0.02 mg/m³, ((measured as mercury)) 8 hours.
Austria	5
rorganic compounds of mercury	GKV_MAK (Austria, 12/2011). Absorbed through skin. Skin sensitiser. Notes: measured as Hg PEAK: 0.08 mg/m³, (measured as Hg), 4 times per shift, 15 minutes. Form: inhalable fraction TWA: 0.02 mg/m³, (measured as Hg) 8 hours. Form: inhalable fraction
Belgium	
rorganic compounds of mercury	Lijst Grenswaarden / Valeurs Limites (Belgium, 4/2014). TWA: 0.02 mg/m³, (as Hg) 8 hours.
Bulgaria	
norganic compounds of mercury	България Министерство на труда и социалната политика и Министерството на здравеопазването (Bulgaria, 1/2012). Limit value 8 hours: 0.01 mg/m³ 8 hours.
Croatia	
inorganic compounds of mercury	MinGoRP GVI/KGVI (Croatia, 6/2013). ELV: 0.02 mg/m³, (as Hg) 8 hours.
Czech Republic	
rorganic compounds of mercury	MZCR PEL/NPK-P (Czech Republic, 1/2013). Absorbed through skin. TWA: 0.02 mg/m³, (as Hg) 8 hours. STEL: 0.15 mg/m³, (as Hg) 15 minutes.
Denmark	
rorganic compounds of mercury	Arbejdstilsynet (Denmark, 10/2012). Absorbed through skin. Notes: calculated as Hg TWA: 0.02 mg/m³, (calculated as Hg) 8 hours.
Estonia	
norganic compounds of mercury	Töökeskkonna keemiliste ohutegurite piirnormid määrus nr 293 (Estonia, 1/2008). Absorbed through skin. Notes: calculated as Hg TWA: 0.03 mg/m³, (calculated as Hg) 8 hours.
Finland	
norganic compounds of mercury	Työterveyslaitos, Sosiaali- ja terveysministeriö (Finland, 3/2014). Absorbed through skin. Notes: calculated as Hg TWA: 0.02 mg/m³, (calculated as Hg) 8 hours.
France	
1	



Water Analysis Test Kit 11/19

SECTION 8: Exposure controls/personal protection

morganic compounds of mercury

Ministère du travail (France, 7/2012). Absorbed through skin. Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits

TWA: 0.1 mg/m³, (as Hg) 8 hours.

Germany

inorganic compounds of mercury

MAK-Werte Liste (Germany, 6/2014). Absorbed through skin. Skin sensitiser. Notes: as Hq

PEAK: 0.16 mg/m³, (as Hg), 4 times per shift, 15 minutes. Form: inhalable fraction

TWA: 0.02 mg/m³, (as Hg) 8 hours. Form: inhalable fraction TRGS900 AGW (Germany, 4/2014). Absorbed through skin. Skin sensitiser.

PEAK: 0.16 mg/m³ 15 minutes. Form: inhalable fraction TWA: 0.02 mg/m³ 8 hours. Form: inhalable fraction

Greece

inorganic compounds of mercury

Υπουργείο Εργασίας και Κοινωνικών Υποθέσεων (Greece, 2/ 2012).

TWA: 0.02 mg/m³, (as Hg) 8 hours.

Hungary

inorganic compounds of mercury

25/2000. (IX. 30.) EüM-SzCsM együttes rendelet (Hungary, 12/2011). Absorbed through skin. Skin sensitiser. Notes: as

TWA: 0.02 mg/m³, (as Hg) 8 hours.

Ireland

inorganic compounds of mercury

NAOSH (Ireland, 12/2011).

OELV-8hr: 0.02 mg/m³ 8 hours.

inorganic compounds of mercury

Ministry of Labour and Social Policy (Italy, 10/2013). Absorbed through skin.

8 hours: 0.02 mg/m³, (come Hg) 8 hours.

Latvia

morganic compounds of mercury

Ministru kabineta - AER (Latvia, 2/2011). Notes: as mercury TWA: 0.02 mg/m³, (as mercury) 8 hours.

Lithuania

morganic compounds of mercury

Lietuvos Higienos Normos HN 23 (Lithuania, 10/2007). Absorbed through skin. Notes: as Hg

TWA: 0.02 mg/m³, (as Hg) 8 hours.

Netherlands

morganic compounds of mercury

MinSZW Wettelijke Grenswaarden (Netherlands, 6/2014). OEL, 8-h TWA: 0.02 mg/m³, (measured as mercury) 8 hours.

Norway

inorganic compounds of mercury

FOR-2011-12-06-1358 (Norway, 1/2013). Skin sensitiser. Notes: calculated as Hq

TWA: 0.02 mg/m³, (calculated as Hg) 8 hours.

Poland

inorganic compounds of mercury

Rozporzadzenie Ministra Pracy i Polityki Spolecznej (Dz.U. 2014 poz. 817) (Poland, 6/2014). Notes: calculated as Hg

TWA: 0.02 mg/m³, (calculated as Hg) 8 hours. Form: vapours

Portugal

inorganic compounds of mercury

Date of issue/Date of revision : 30.11.2016

Instituto Português da Qualidade (Portugal, 3/2007). Absorbed through skin. Notes: expressed as Hg

TWA: 0.025 mg/m³, (expressed as Hg) 8 hours.

Romania

Water Analysis Test Kit 12/19

SECTION 8: Exposure controls/personal protection

morganic compounds of mercury

EU OEL (Europe, 12/2009). Notes: list of indicative

occupational exposure limit values

TWA: 0.02 mg/m³, ((measured as mercury)) 8 hours.

Slovakia

rorganic compounds of mercury

Nariadenie vlády SR c. 355/2006 (Slovakia, 12/2011).

TWA: 0.1 mg/m³, (Mercury and its divalent inorganic compounds including mercuric oxide and mercuric chloride, as Hg) 8 hours.

Slovenia

morganic compounds of mercury

Pravilnik o varovanju delavcev pred tveganji zaradi

izpostavljenosti kemičnim snovem pri delu (Slovenia, 12/2010). TWA: 0.02 mg/m³, (measured as Hg) 8 hours.

Spain

inorganic compounds of mercury

INSHT (Spain, 1/2014). Absorbed through skin. Notes: As Hg

TWA: 0.02 mg/m³, (as Hg) 8 hours.

Sweden

morganic compounds of mercury

AFS 2011:18 (Sweden, 12/2011). Absorbed through skin.

Notes: as Hg

TWA: 0.03 mg/m³, (as Hg) 8 hours.

Switzerland

inorganic compounds of mercury

SUVA (Switzerland, 1/2014). Absorbed through skin. Skin

sensitiser. Notes: calculated as Hg

STEL: 0.16 mg/m³, (calculated as Hg) 15 minutes. Form:

Inhalable dust (total dust)

TWA: 0.02 mg/m³, (calculated as Hg) 8 hours. Form: Inhalable

dust (total dust)

Turkey

inorganic compounds of mercury

TR ISGGM OEL (Turkey, 12/2013).

TWA: 0.02 mg/m³, (measured as mercury) 8 hours.

United Kingdom (UK)

inorganic compounds of mercury

EH40/2005 WELs (United Kingdom (UK), 12/2011).

TWA: 0.02 mg/m³, (as Hg) 8 hours.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

No DELs available.

Predicted effect concentrations

No PECs available.

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.



Water Analysis Test Kit 13/19

SECTION 8: Exposure controls/personal protection

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. < 1 hour (breakthrough time): disposable vinyl

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: overall

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: None assigned.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

: Clear. Yellowish. Colour Odour : Not available.

pH 7 [Conc. (% w/w): 100%]

Melting point/freezing point

Initial boiling point and

: 100°C

: Not available.

boiling range

: Not available. Flash point Upper/lower flammability or : Not available.

explosive limits

Relative density

: Easily soluble in the following materials: cold water and hot water. Solubility(ies)

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature

Date of issue/Date of revision : 30.11.2016

Not available.



Water Analysis Test Kit

SECTION 9: Physical and chemical properties

VOC content 0 % (w/w)

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
inorganic compounds of mercury	LD50 Dermal	Rat	75 mg/kg	-
	LD50 Oral	Rat	26 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Conclusion/Summary: Not available.

<u>Sensitiser</u>

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date of revision : 30.11.2016

A MacDermid Performance Solutions Business
A Platform Specialty Products Company

Water Analysis Test Kit 15/19

SECTION 11: Toxicological information

Product/ingredient name	Category	Route of exposure	Target organs
inorganic compounds of mercury	Category 2	Not determined	Not determined

Aspiration hazard

Not available.

Information on likely

: Not available.

routes of exposure

Potential acute health effects

Inhalation : May cause respiratory irritation.

Ingestion: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Eye contact: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion: No specific data.Skin contact: No specific data.Eye contact: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Not available.

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
inorganic compounds of mercury	Acute LC50 0.001 to 0.002 mg/l Fresh water Acute LC50 172 to 347 µg/l Fresh water	Crustaceans - Moina macrocopa Fish - Pimephales promelas	48 hours 96 hours

Conclusion/Summary: Not available.

Date of issue/Date of revision : 30.11.2016



Water Analysis Test Kit 16/19

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

: Not available. **Mobility**

12.5 Results of PBT and vPvB assessment

: Not applicable. **vPvB** : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste Yes. **European waste catalogue (EWC)**

Waste code	Waste designation	
16 03 03*	inorganic wastes containing dangerous substances	

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Water Analysis Test Kit 17/19

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Date of issue/Date of revision : 30.11.2016

Annex XVII - Restrictions: Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles Other EU regulations

Europe inventory : All components are listed or exempted.

National regulations

Austria Belgium

Bulgaria

Croatia

Czech Republic

Denmark Estonia

Water Analysis Test Kit 18/19

SECTION 15: Regulatory information

Finland France

Germany

Hazard class for water : 2 Appendix No. 4

Greece Hungary Ireland Italy

Latvia Lithuania

Product/ingredient name	List name	Name on list	Classification	Notes
inorganic compounds of mercury	Occupational Exposure Values	gyvsidabrio junginiai, išskyrus nurodytus kitur šiame sąraše kaip Hg	Repro. R, Muta. M	-

: This product contains substances for which Chemical Safety Assessments are still

Netherlands

Norway

Poland

Portugal

Romania

Slovakia

Slovenia

Spain

Sweden

Switzerland

Turkey

United Kingdom (UK)

15.2 Chemical safety

required. assessment

SECTION 16: Other information

Date of printing 10.12.2016 Date of issue/ Date of : 30.11.2016

revision

Date of previous issue : 29.11.2016

Date of issue/Date of revision : 30.11.2016

Version 2.11

Notice to reader

Indicates information that has changed from previously issued version.

Abbreviations and : ATE = Acute Toxicity Estimate

acronyms CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification **Justification**



Water Analysis Test Kit	19/19		
STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	Expert judgment Expert judgment Expert judgment		
<u>Europe</u>			
Full text of abbreviated H statements	 : H300 Fatal if swallowed. H310 Fatal in contact with skin. H330 Fatal if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. 		
Full text of classifications [CLP/GHS]	: Acute Tox. 1, H310 ACUTE TOXICITY (dermal) - Category 1 Acute Tox. 2, H300 ACUTE TOXICITY (oral) - Category 2 Acute Tox. 2, H330 ACUTE TOXICITY (inhalation) - Category 2 ACUTE TOXICITY (inhalation) - Category 1 Acute Tox. 2, H330 ACUTE TOXICITY (inhalation) - Category 2 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3		
Full text of abbreviated R phrases	: R26/27/28- Very toxic by inhalation, in contact with skin and if swallowed. R20/21/22- Harmful by inhalation, in contact with skin and if swallowed. R33- Danger of cumulative effects. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.		
Full text of classifications [DSD/DPD]	: T+ - Very toxic Xn - Harmful N - Dangerous for the environment		

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Date of issue/Date of revision : 30.11.2016

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Fernox SDS CLP Europe

