

Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____



Nominal length : 48 in. (1 220 mm) Dia. : 1 in. (26 mm)

ORDERING INFORMATION

Order code: 65478
 Description: LED/T8/S4/15W/840/48/STD
 UPC: 69549654785
 Case quantity: 25

PERFORMANCE DATA

Shape: T8
 Base: G13
 Starting method: Instant, Rapid & Program Start
 Lamp voltage (VAC): 120 V - 277 V / 347 V
 Color temperature (K)**: 4 000
 Average life (L70 hours): 50 000
 CRI: >80
 Beam angle (°): >240
 Operating temperature range: -20°C / -4°F to 45°C / 113°F
 DLC Listed: DLC Standard

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %

Order code	Average System Watts (W)			Initial Lumens (lm)*		
	LBF	NBF	HB	LBF	NBF	HB
65478	16	18	26	1 800	2 100	2 850



DAMP



COMPLIANT



NO
MERCURY



WARRANTY



CAUTIONS

THIS LAMP OPERATES ON INSTANT START, RAPID START AND MANY PROGRAM START ELECTRONIC BALLASTS.
 Direct replacement for 25, 28, 30 and 32 watts lamps only. Risk of fire. Do not install this lamp in a pre-heat luminaire. Risk of electric shock – for use in damp locations.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

ORDERING INFORMATION

Order code: 65478
 Description: LED/T8/S4/15W/840/48/STD
 UPC: 69549654785
 Case quantity: 25

Ballast Compatibility List - 120-277 V (1/2)

Ballast Description				1 Lamp		2 Lamps		3 Lamps		4 Lamps	
Brand	Order Code	Number of lamps	Starting Method	Input Voltage							
				120 V	277 V	120 V	277 V	120 V	277 V	120 V	277 V
Arcata	ACT4P32ISUNV	4	IS								
Advance	ICN-2P32-N	2	IS								
	IOPA-2P32-N	2	IS								
	RCN-2S32-SC	2	PS								
	REL-2P32-SC	2	IS								
	ICN-4P32-SC	4	IS								
ESPEN	VE232MVHIP	2	IS								
	VE232MVHIPE	2	IS								
	VE232MVHIPHE	2	IS								
	VE232MVHIPL	2	IS								
	VE432MVHIP	4	IS								
	VE432MVHIPE	4	IS								
	VE432MVHIPHE	4	IS								
Fusion	FB232MVE	2	IS								
	FB232MVE-HE	2	IS								
	FB232MVE-LHE	2	IS								
	FB332MVE	3	IS								
	FB432MVE	4	IS								
	FB432MVE-HE	4	IS								
GE	GE232MAX-N/ULTRA	2	IS								
	GE232-MVPS-L	2	PS								
	GE-232-MVPS-H	2	PS								
	GE332MV-N-DIY	3	IS								
Green Hill	GH4P32ISUNV	4	IS								
Halco	EP232IS/H/MV/HE	2	IS								
	EP332IS/L/MV/HE	3	IS								
	EP332IS/MV/MC	3	IS								
	EP432IS/L/MV/HE	4	IS								
	EP432IS/MV/MC	4	IS								
Howard	EP4/32IS/MV/MC/HE	4	IS								
Huafeng	ENI-T8-32-P2SC-N	2	IS								
	ENI-T8-32-P4MC-N	4	IS								
Keystone	KTEB-232-UV-IS-N-P	2	IS								
	KTEB-332-UV-IS-N-P	3	IS								
	KTEB-432-UV-IS-N-P	4	IS								

 compatible  non-compatible  N/A

NOTE: STANDARD's ballast testing is limited to the above mentioned ballasts, however ballasts of the appropriate type that are manufactured in accordance to ANSI standards should be compatible with STANDARD LED fluorescent replacement lamps. Testing in each application is suggested. For complete ballast compatibility list visit www.standardpro.com.

STANDARD[®]

ORDERING INFORMATION

Order code: 65478
 Description: LED/T8/S4/15W/840/48/STD
 UPC: 69549654785
 Case quantity: 25

Ballast Compatibility List - 120-277 V (2/2)

Ballast Description				1 Lamp		2 Lamps		3 Lamps		4 Lamps	
Brand	Order Code	Number of lamps	Starting Method	Input Voltage							
				120 V	277 V	120 V	277 V	120 V	277 V	120 V	277 V
Pacific	EB-332IS-U	3	IS								
	EB-432IS-U	4	IS								
Premium	BB-T8/UVH-2x32	2	IS								
	BB-T8/UVH-3x32	3	IS								
Robertson	RSW240T12120	2	RS								
Standard	61113 - E232T8IS120/N/AS	2	IS								
	61124 - E232T8IS120/N/AS/BULK	2	IS								
	59770 - E432T8IS120/H/90C	4	IS								
	61120 - E432T8IS120/L/AS	4	IS								
	61127 - E432T8IS120/L/AS/BULK	4	IS								
	61114 - E432T8IS120/N/AS	4	IS								
	61125 - E432T8IS120/N/AS/BULK	4	IS								
Sunpark	SL15T	2	RS								
Universal	B232IUNVHP-N	2	IS								

Ballast Compatibility List - 347 V

Ballast Description				1 Lamp	2 Lamps	3 Lamps	4 Lamps
Brand	Order Code	Number of lamps	Starting Method	Input Voltage			
				347 V			
Fusion	FB232347E-HE	2	IS				
	FB232347E-L	2	IS				
	FB432347E-HE	4	IS				
	FB432347E-L	4	IS				
Standard	60076 - E232T8IS347/H/90C	2	IS				
	58278 - E232T8IS347/L/BULK	2	IS				
	10293 - E232T8IS347/N	2	IS				
	31549 - E232T8IS347/N/BULK	2	IS				
	31036 - E432T8IS347/L	4	IS				
	59771 - E432T8IS347/L/BULK	4	IS				
	10294 - E432T8IS347/N	4	IS				
	31552 - E432T8IS347/N/BULK	4	IS				
	59771 - E432T8IS347/H/90C	4	IS				
Ultrasave	MR232347	2	-				

 compatible  non-compatible  N/A

NOTE: STANDARD's ballast testing is limited to the above mentioned ballasts, however ballasts of the appropriate type that are manufactured in accordance to ANSI standards should be compatible with STANDARD LED fluorescent replacement lamps. Testing in each application is suggested. For complete ballast compatibility list visit www.standardpro.com.

STANDARD[®]