## 

## SPECIFICATIONS

- SOLID METAL CONSTRUCTION >
- 4-IN-1 ADJUSTABLE LATCH FOR DRIVE-IN AND SQUARE MORTISE INSTALLATIONS WITH ADJUSTABLE BACKSET: 2-3/8" (60 mm) - 2-3/4" (70 mm)
- FITS STANDARD DOOR THICKNESS: 1-3/8" (35 mm) 1-3/4" (45 mm) >
- STANDARD BORE HOLES: 2-1/8" (54 mm) >
- 1-3/4" x 2-1/4" FULL LIP CORNER RADIUS "D" STRIKE >
- WR5 5-PIN KEYWAY >
- KEYING SERVICE AVAILABLE >
- FIRE RATING DOES NOT APPLY TO ENTRY FUNCTION
- > COMPATIBLE WITH 5" BACKSET DEADLATCH



PERSPECT



9 C

REVERSIBLE

**BUILDERS SERIES** RESIDENTIAL LEVERSET

**25 YEARS MECHANICAL & 5 YEARS FINISH WARRANTY** 

- 20 MINUTE OPTIONAL FIRE RATING 1-3/8" - 1-3/4" (35 mm - 45 mm) 2-1/16" (52 mm) 2-1/16" (52 mm) 2-5/8' (66 mm) . (25 mm (25 mm) 9/16" [14 mm] Ű Γ m m 4" (102 i 4-IN-1 DRIVE-IN/SQUARE MORTISE (25mn (25mm) 1-3/4" (44mm) Ø 7/8 (22mm) 2-1/4" (57mm) Ø, Ø ADJUSTABLE 2-3/4" (70mm) OR 2-3/8" (60mm) ADJUSTABLE (O)2-3/4" (70mm) ➤ OR 2-3/8" (60mm) (25mm) . (25mm) FULL LIP RADIUS STRIKE 4-IN-1 ENTRY LATCH 4-IN-1 PRIVACY/PASSAGE LATCH
  - MEASUREMENTS SUBJECT TO A 3% VARIANCE

MEASUREMENTS ARE FOR REFERENCE ONLY. TAYMOR RESERVES THE RIGHT TO CHANGE THE PRODUCT SPECS WITHOUT NOTICE. FOR PRODUCT WARRANTY, PLEASE VISIT TAYMOR WEBSITE FOR DETAILS www.taymor.com

PERSPECTIVE BUILDER PACK	ENTRY - KD	PRIVACY	PASSAGE	DUMMY
POLISHED BRASS 3	36-D6210PB	36-D6203PB	36-D6205PB	36-6211PB
SATIN NICKEL 15	36-D6210SN	36-D6203SN	36-D6205SN	36-6211SN
SATIN CHROME 26D	36-D6210SC	36-D6203SC	36-D6205SC	36-6211SC
CASE QTY 20				

