SPECIFICATION SHEET

Designed with simplicity in mind, the BU2 range hood models are made to exacting standards and offer the most for the money.

SIZE	WHITE	WHITE WITH BLACK CONTROL	BLACK	STAINLESS	GREASE FILTER (replacement)	CHARCOAL FILTER
24 in.	-	BU224WH	-	BU224SS	BP29	41F
30 in.	BU230WW	BU230WH	BU230BL	BU230SS	BP29	41F

PERFORMANCE								
Duct Orientation	Size	Damper	Sones on high speed	CFM on high speed				
Vertical - Rectangular	3¼ in. x 10 in.	Included	6.5	160				
Horizontal - Rectangular	31/4 in. x 10 in.	Included	6,5	160				

FEATURES					
Control type	2-speed rocker switch				
Delay off	no				
Filter Clean Reminder	no				
Heat Sentry™	no				
Lighting	1-level 75-watt bulb (not included)				
Grease Filter	Aluminum (Qty. 1)				
ENERGY STAR®	no				
Recirculation	Charcoal filter sold separately				

AC INPUT

120 V, 60 Hz - 2.5 AMPS

OPTIONAL ACCESSORIES 31/4 in. x 10 in. to 6-in. 411 Round Duct Transition 7-in. Round Damper BP87 7-in. Round Adapter Plate SR680508

MOUNTING HEIGHT


18 in. to 24 in. from cooktop to bottom of hood

LIMITED WARRANTY


1-year

(See installation manual for full warranty text.)

FOR INDOOR USE ONLY











HVI-2100 CERTIFIED RATINGS comply with newtesting technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

99045919A