



# IRON GUARD®

Krylon® Industrial Iron Guard® is the first and only latex paint in the industrial market. This latex (not water-reducible!) paint provides a high gloss and excellent color retention and appearance. Soap and water clean-up reduces costly downtime, costly materials and keeps production moving.

- ✓ Topcoat anytime with no lifting
- ✓ Fast drying
- ✓ Soap & water clean-up
- ✓ Interior/exterior use

## INDUSTRIAL USE ONLY!

krylonindustrial.com  
1-800-247-3266

### RECOMMENDED USES

- Metal
- Wood
- Masonry
- Plaster
- Most Plastics
- Plastic Foam

### SURFACE PREPARATION

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** For more information, contact your local health authority. Remove dirt, grease, wax, moisture, rust and loose paint from surface. Scuff-sand rusted, glossy or hard surfaces. Prime bare or rusted metal. For maximum corrosion resistance, prime first with Iron Guard Primer. Protect adjacent areas from overspray (overspray can be removed with soap and water up to 20 minutes).

### CLEAN-UP

Clean-up is easy with soap and water for up to 20 minutes. Lacquer thinner when dry. Clean spray valve immediately after use by turning can upside-down and spraying until only clear gas comes out. Dispose of in accordance with local, state or federal regulations.

### TECHNICAL DATA

<b>Vehicle</b>	Acrylic Latex Enamel
<b>Finish</b>	Max Flat, Satin, Gloss
<b>Flash Point</b>	-20°
<b>Weight/Gallon</b>	7.41 lb/gal
<b>VOC/MIR</b>	.49
<b>Spread Rate</b>	12-15 sq. feet
<b>Shelf Life</b>	60 months
<b>Drying Time</b>	To Touch: 20 minutes To Recoat: Anytime To Handle: 1 hour
<b>Dry Heat Resistance</b>	<150°
<b>Gas Resistance</b>	Softens with gas
<b>Oil Resistance</b>	Pass
<b>Clean Up</b>	Mineral Spirits, Please follow suppliers instructions
<b>Net Weight/Can Size</b>	12 oz. / 16 oz.

### APPLICATION

#### APPLICATION CONDITIONS

Use at 70°F for best operation. Shake can for 2 minutes after ball within begins to rattle. Repeat for 10 seconds after each minute of use. Test spray on inconspicuous area or scrap piece to check compatibility. For a smooth, professional finish, spray 10" to 12" from surface in a sweeping motion. Avoid runs and drips by applying several thin coats, rather than one heavy coat. Dries to touch in 20 minutes. Can be handled in 1 hour. Can be recoated at any time.

### CAUTIONS

**FOR INDUSTRIAL USE ONLY.** Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

**Note:** The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.

The information and recommendations set forth in the Product Data Sheet are based upon tests conducted by or on behalf of Krylon® Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon® Industrial dealer or representative to obtain the most recent Product Data Sheet.