

S29394

54W/LED/HID/5000K/100-277V/EX39 54 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size						
Length	Width	Depth				
17.3 inch	9.25 inch	9.25 inch				

Optional accessory: In-line surge protector 80-929



S29394

Item	Product	UPC Input		Watts	Operating	Incandescent	Fluorescent		
Number	Line	Voltage			Frequency	Equivalent	Equivalent		
S29394	Hi-Pro	045923293948	100 - 277	54	50/60Hz	300W	85W		

HID Equivalent	Base	ANSI Base	Lamp Code				able/Non- nmable Finish		MOL In Inches		DD In ches	
250W	Mogul Extended	EX39	54W/LED/HID/5000K/100- 277V/EX39			00-	Non-D	immable	White	10-3/4"	3.	.69"
Initial Lumens	Average Rat Hours	ted I	Kelvin Temp	Color	CRI	l Bea	m Spread Deg	Operating Temperature				Pack
7200	50000		5000	Natural Light	80+	+	300	-20C (-4F) to a maximu +65C (+149F)			f	12
Package Type	CEC Sta	atus	DLC ID:		F	RoHS Compliant		UL Classification)	Warranty	
Вох	Lawful for s Califor		PLGVDTP7L3LM DLC Search			Yes		cULus - Wet Location Rated		Year Limited		



HID

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

ANSI

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

Dimmable/Non-



MOL In

MOD In

©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051