

UV TREATED POLYPROPYLENE TAPE



DESCRIPTION

This tape is made of a special UV resistant treated film and coated with a very aggressive solvent based acrylic adhesive. Its combination of film and adhesive will deliver performance under a variety of stressed applications.

MAIN FEATURES

- High shear adhesive.
- Resist to solvents and chemicals.
- Excellent resistance to UV and weathering.
- Strong holding power, remains stuck over time.
- Provides permanent bond to most surfaces.

APPLICATIONS

- Splicing and tabbing of paper, polyethylene, polyester, polypropylene and PVC in the web manufacturing process.
- Critical outdoors application.
- Greenhouse film repair.

PERMANENT BOND

HIGH SHEAR ADHESIVE

TECHNICAL DATA

Colour	Clear(00), Red(02) and White(10)
Backing	U.V. Resistant Polypropylene Film
Adhesive.....	Solvent based Acrylic
Thickness	3 mil
Adhesion to steel.....	40 oz/in
Tensile strength	30 lb/in
Elongation	140%
Temperature Resistance	100°C (212°F)

STOCK SIZE

48 mm x 66 m — 24 rolls/case
72 mm x 66 m — 12 rolls/case

Please note:

The technical characteristics quoted are averages only and may vary within industry tolerances.

The final user must assure product suitability for the application and assumes all risks and liabilities.