


Date: \_\_\_\_\_  
 In hands date of project: \_\_\_\_\_  
 Project name/Number: \_\_\_\_\_  
 Name of distributor: \_\_\_\_\_  
 Client #: \_\_\_\_\_  
 Name of end user: \_\_\_\_\_

## ORDERING INFORMATION

Order code: 66178  
 Description: LED/A19/S4/6W/40K/STD  
 UPC: 69549661783  
 Case quantity: 6 / 48



MOL : 4 11/32 in. (110 mm) Dia. : 2 3/8 in. (60 mm)

## PERFORMANCE DATA

Shape: A19  
 Wattage (W): 6  
 Base: E26  
 Lamp voltage (VAC): 120  
 Colour temperature (K)\*\*: 4 000  
 Average life (L70 hours): 25 000  
 Initial lumens (lm)\*: 480  
 Initial lumens per watt (lm/W): 80  
 CRI: 80  
 Beam angle (°): 220  
 Power factor: 0.98  
 THD (%): 17  
 Operating temperature range: - 20 °C / - 4 °F to 45 °C / 113 °F

\*Initial lumens range: +/- 10 %

\*\*Typical colour temperature range: +/- 5 %

## DIMMER COMPATIBILITY LIST

<b>Legrand</b>	HCL453P
<b>Cooper</b>	AAL06, SLC03P
<b>Leviton</b>	6615, 6674, DSM10-1LZ, IPE04-1LZ, IPL06
<b>Lutron</b>	AYCL-253P, DVELV-300P, MACL-153P, PD-6WCL, SELV-300P



## CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electrical shock – do not use where directly exposed to water or weather.
- Suitable for use in totally enclosed luminaires.
- Suitable for use in damp locations.
- Do not open – no user serviceable parts inside.
- Use only on 120 VAC, 60Hz circuits.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.
- Compatible with most dimmers.
- For complete dimmer and warranty information visit [www.standardpro.com](http://www.standardpro.com).

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Signature: \_\_\_\_\_

Date: \_\_\_\_\_

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
 Data is based upon tests performed in a controlled environment and representative of relative performance.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

November 1, 2017

**STANDARD**<sup>®</sup>