

Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____

ORDERING INFORMATION

Order code: 66156
 Description: LED/T8/9W/840/24/BYP/120-277/ND/STD
 UPC: 69549661561
 Case quantity: 25

PERFORMANCE DATA

Shape: T8
 Base: G13
 Install method: Ballast bypass
 Watts (W): 9
 Lamp voltage (VAC): 120 V - 277 V
 Color temperature (K)**: 4 000
 Initial Lumens (lm)*: 1 150
 Initial lumens per watt (lm/W): 128
 Average life (L70 hours): 50 000
 CRI: 82
 Dimmable: No
 Operating temperature range: -20°C / -4°F to 45°C / 113°F

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %



*This product complies with UL1598C Standard for LED luminaire Retrofit kits. Not suitable for hazardous location.

CAUTIONS

Only for ballast bypass installation in 120-277V applications. Not for use in 347V direct line voltage applications.
 Direct replacement for 15 & 17 watts T8 lamps only. Do not use with dimmers. Not for emergency lighting. Risk of electric shock – for use in damp locations.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____

Company: _____

Signature: _____

Date: _____

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
 Data is based upon tests performed in a controlled environment and representative of relative performance.
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

September 17, 2018

STANDARD®



MOL: 23 3/4 in. (604 mm) Dia.: 1 in. (26 mm)