

Technical Information Bulletin

LED Lamps



Date: _____ Name of distributor: _____
In hands date of project: _____ Client #: _____
Project name/Number: _____ Name of end user: _____

ORDERING INFORMATION


Order code: 66763
Description: C12/S2/4.5W/27K/CL/STD
UPC: 69549667631
Case quantity: 24 / 48

PERFORMANCE DATA

Shape: C12
Base: E26
Watts(W): 4.5
Volts (VAC): 120
Colour temperature (K)**: 2 700
Average life (L70 hours): 15 000
Initial lumens (lm)*: 322
Initial lumens per watt (lm/W): 72
CRI: 82
Beam angle: 260
Power factor: 0.98
Operating temperature range: -20 °C to 45 °C (-4 °F to 113 °F)

*Initial lumens range: +/- 10 %

**Typical colour temperature range: +/- 5 %



COMPATIBLE DIMMERS

Legrand	HCL453P, RH703PTUTC
Cooper	AAL06, DAL06P, SLC03P
Leviton	6674, DSL06-1LZ, DSM10-1LZ, IPL06
Lutron	AYCL-253P, CTCL-153P, DVCL-253P, DVELV-300P, MACL-153P



CAUTIONS

- Turn power off before inspection, installation, or removal.
- Risk of electric shock – do not use where directly exposed to water or weather.
 - Not for use in totally enclosed luminaires.
 - Suitable for use in damp locations.
 - Added weight of the device may cause instability of a free-standing portable luminaire. Use only with a portable table lamps in which the distance from the bottom of the base to the top of the lamp holder does not exceed three (3) times the minimum base diameter.
 - Do not open – no user serviceable parts inside.
 - Use only on 120 VAC, 60 Hz circuits.
 - This device is not intended for use with emergency exit fixtures or emergency exit lights.
 - For complete dimmer and warranty information visit www.standardpro.com.
 - 3 Years Limited Warranty.
 - Operating temperature: - 20°C to 45°C (- 4°F to 113°F)

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: _____
Company: _____
Signature: _____

Date: _____

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.
Data is based upon tests performed in a controlled environment and representative of relative performance.
Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.