## **Technical Information Bulletin** PRO LED Lamps



Date:	Name of distributor:	
In hands date of project:	Client #:	
Project name/Number:	Name of end user:	

## **ORDERING INFORMATION**

Order code:	66275
Description:	A19/9.8W/27K/GU24/PRO/STD
UPC:	69549662759
Case quantity:	6 / 48



## PERFORMANCE DATA

Shape:	A19
Base:	GU24
Watts(W):	9.8
Volts (VAC):	120
Colour temperature (K)**:	2 700
Average life (L70 hours):	25 000
Initial lumens (lm)*:	814
Initial lumens per watt (lm/W):	83
CRI:	83
Beam angle:	220
Power factor:	0.99
Operating temperature range:	-20 °C to 45 °C (-4 °F to 113 °F)

\*Initial lumens range: +/- 10 % \*\*Typical colour temperature range: +/- 5 %



This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

## CAUTIONS

- Turn power off before inspection, installation, or removal.
  Risk of electrical shock do not use where directly exposed to water or weather.
  Suitable for use in totally enclosed luminaires.
  Suitable for use ready serviceable parts inside.
  Use only on 120 VAC, 60Hz circuits.
  This device is not intended for use with emergency exit fixtures or emergency exit lights.
  Suitable for use with dimmers.
  For complete warranty and dimmer information visit www.standardpro.com.
  Years Limited Warranty.

Qty	Description	Price
I accept the spec	cifications of the luminaire configuration men	ioned above.
Name:		
Company:		
Signature:		Date:

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.