
Bell & Gossett NRF Booster Pumps for the Home

NRF Series Iron Body Booster Pumps




Great for home heating applications: Choose from five different models, including the new 3-speed models, NRF-25, -36 & -45. Except for the NRF-45, all models share the same "A" dimension as the famous series 100 pumps. Rated to 150 psi at 225° F. System (water) lubricated.



NRF Series Pump Ordering Guide Pumps include replacement flange gaskets. Order flanges separately.

| Model No. | Red-Colored, | Max. | Motor Characteristics | | | Δ | В | • | Weight | ORDER |
|-----------|-----------------------------------|------|-----------------------|-------|------|--------|---------|--------|---------|---------|
| Model No. | Iron Body Construction | RPM | Max HP | Phase | Amps | A | D | С | in Ibs. | NO. |
| NRF-22 | 1-speed, standard heating | 2940 | 1/8 | | .80 | 6-3/8" | 6-3/16" | 5-1/8" | 9.3 | BH1050 |
| NRF9F/LW | 1-speed, for zoning & radiant | 2800 | 1/16 | | .40 | 6-3/8" | 6-3/16" | 5-1/8" | 9.3 | BH1049 |
| NRF-33 | 1-speed, standard heating | 2950 | 1/6 | 115V | 1.10 | 6-3/8" | 5-9/16" | 4-7/8" | 10.4 | BH1050D |
| NRF-25 | 3-speed , standard heating | 2950 | 1/6 | 1 ph | 1.20 | 6-3/8" | 6-3/16" | 5-1/8" | 10.4 | BH1050F |
| NRF-36 | 3-speed , standard heating | 3300 | 1/3 | | 2.30 | 6-3/8" | 6-7/8" | 5-3/4" | 13.1 | BH1050G |
| NRF-45 | 3-speed , standard heating | 3300 | 1/3 | | 2.30 | 8-1/2" | 7-3/8" | 5-3/4" | 14.5 | BH1050H |


NRF Series Pump Dimension Guide



Pump Isolation Flanged Ball Valves

Isolation Ball Valves Make Pump Repair and Replacement Easy!

Install these isolation valves in place of the standard pump flanges. Turn valve "off" to remove pump for repair or replacement — No more need to drain system!



| Threaded Isolation Valves | Order No. | |
|----------------------------------|--------------|--|
| 34" pipe thread | BI2700 | |
| 1" pipe thread | BI2701 | |
| 11/4" pipe thread | BI2702 | |
| 11/2" pipe thread | BI2702B | |


Set of two

| Sweat Isolation Valves | Order No. |
|----------------------------------|--------------|
| 3/4" sweat copper | BI2705 |
| 1" sweat copper | BI2706 |
| 1¼" sweat copper | BI2707 |
| 1½" sweat copper | BI2707B |

Standard Pump Flange Guide

Note: The NRF-45 uses 1", 1-1/4" and 1-1/2" flanges.

| Flange Pipe Size | Red Flange Order No. Includes bolts/nuts | Flange Gaskets Order No. |
|---------------------|--|-----------------------------|
| 3/4" | BG1005 | |
| 1" | BG1010 | BG1185 |
| 1-1/4" | BG1015 | (set of 2) |
| 1-1/2" | BG1020 | |
| Fastener Pac | k (4 bolts, 4 nuts, 2 gaskets) | BG1561H |



Pipe-to-Pump Flange Side View with Bolts

Two Flange gaskets included with new pump.

If needed, order a Fastener Pack (4 bolts, 4 nuts and 2 gaskets) separately.