
Pfister

Pfirst Series™

Kitchen Faucet

G135-1000 Finish(*PC*) ☐ G135-100S Finish(*SS*) ☐ G135-1100 Finish(*PC*) ☐

G135-2000 Finish(*PC*) ☐ G135-4000 Finish(*PC*) ☐ G135-4100 Finish(*PC*) ☐ G135-5000 Finish(*PC*) ☐





Specifications

Features

- 1.8 GPM Flow Rate
- Acrylic Windsor® Handles (1100 & 4100 Only)
- Blade Handles (2000 & 5000 Only)
- Includes Metal Supply Nuts
- 3-Hole Installation (100*, 1100, & 2000 Only)
- 4-Hole Installation (4000, 4100, & 5000 Only)
- White Side Spray (4000, 4100, & 5000 Only)
- Washerless Valves
- Pforever Warranty®

Code Compliance

• 1/4 Turn Washerless Valves

• 3 or 4-Hole Installation

Pfister products are designed and manufactured in compliance with the following standards and codes:



- CSA B125 Certified
- ASME A112.18.1

• Two-Handle

- NSF 61/9 Annex G (Low lead)
- Cal Green Compliant
- EPA Watersense Certification 1.8 gpm, 6.8 L/Min
- ADA Compliant-ANSI A117.1 (Lever handles only) (1100, 2000, & 5000 Only)
- ASME A112.18.3 (Backflow Prevention)







Dimensions

