



S11907

7W/LED/T5/830/BP

7W T5 LED; Miniature bi-pin base; 3000K; 50000 Average rated hours; 700 Lumens; 120-277V; Type B; Ballast Bypass; Double Ended Wiring



Features

- No ballast or external driver required
- Available in 6", 9", 12", & 21"
- Direct wire 120-277V line voltage
- Double ended wiring
- NSF Approved
- PET Shatterproof coated
- 5 year Limited warranty

S11907

Replaces F13T5/WW lamps

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape	
S11907	045923119071	120-277	7	50/60Hz	13W	0.90	T5	
Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable		Finish	MOL In Inches	MOD In Inches	Initial Lumens
Miniature Bi-Pin	G5	7W/LED/T5/830/BP	Non-Dimmable		Frosted	20-29/32"	0-5/8"	700
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	
50000	3000	Warm White	80	240	-25C (-13F) to a maximum of +45C (+113F)	10	Lawful for sale in California	
Material	RoHS Compliant	UL or ETL Listed			UL Classification			Warranty
Glass	Yes	Yes			cULus Classified - Damp Location Rated			5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051