

S18450

13T8/U1-G13/LED/830/DUAL 13W T8 U-Bend LED; Type A + B; 50000 Hours; Medium bi-pin base; 1800 Lumens; 3000K; Ballast Dependant or Ballast Bypass; Single or Double Ended Wiring

Features

- Direct replacements for fluorescent T8 U-bend lamps in existing fixtures with or without ballasts
- Ballast compatible and ballast bypass in one lamp
- Bypass mode works in single or double ended wiring
- 120-277V in bypass modeNSF Approved

S18450

View:

Ballast Compatibility Chart Emergency Ballast Compatibility Chart

Item Number	UPC Voltage		Voltage	Watts		rating luency		rescent iivalent	Power Factor	Lamp Shape
S18450	04592	045923184505 120-277			50/	60Hz	3	31W	0.90	Т8
Base	ANSI Base	Lamp Code			Dimmable/Non- Dimmable		Finish MOL In Inches		MOD In Inches	Leg Spacing
Medium Bi- Pin	G13	13T8/U1-G13/LED/830/DUAL		Non-Dimmable		White	22.59"	1.00"	1.625"	
Initial Lumens	Average Rated Hours		Kelvin Temp	Color	CRI Beam Spr Deg		ead Operating 1		Temperature	Pack
								20C (4E) to	a mavimum	of

Initial Lume	ns Hours	Kelvin Temp	Color	CRI	Deg	Operating Temperature	Pack
1800	50000	3000	Soft White	80	160	-20C (-4F) to a maximum of +45C (+113F)	24
Package Type	CEC Status	DLC ID:	Material	Rol Comp	· FII	UL Classification \	Warranty

Box

in California

Lawful for sale PLU3DBV5TZQG **DLC Search**

Plastic

Yes

Yes

cULus Listed for Type A; cULus Classified for Type B - Damp Location Rated

5 Year Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051