



S18453

13T8/U1-G13/LED/850/DUAL
13W T8 U-Bend LED; Type A + B; 50000 Hours; Medium bi-pin
base; 2000 Lumens; 5000K; Ballast Dependant or Ballast
Bypass; Single or Double Ended Wiring



Features

- Direct replacements for fluorescent T8 u-bend lamps in existing fixtures with or without ballasts
- Ballast compatible and ballast bypass in one lamp
- Bypass mode works in single or double ended wiring
- 120-277V in bypass mode
- NSF Approved

S18453

View:

[Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Power Factor	Lamp Shape
S18453	045923184536	120-277	13	50/60Hz	31W	0.90	T8

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing
Medium Bi-Pin	G13	13T8/U1-G13/LED/850/DUAL	Non-Dimmable	White	22.59"	1.00"	1.625"

Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack
2000	50000	5000	Natural Light	80	160	-20C (-4F) to a maximum of +45C (+113F)	24

Package Type	CEC Status	DLC ID:	Material	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Box	Lawful for sale in California	PLL0X0VFL6OP DLC Search	Plastic	Yes	Yes	cULus Listed for Type A; cULus Classified for Type B - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051