



S29993

10T8/LED/36-850/DR
10W T8 LED; 5000K; Medium Bi Pin base; 50000 Average
rated hours; 1450 Lumens; Type A; Ballast dependent



Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- Compatible with emergency ballasts*
- 25watt Fluorescent equivalency
- 5 year Limited warranty

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

S29993

Ballast required

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29993	045923299933	10	25W	T8	Medium Bi-Pin	G13	10T8/LED/36-850/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	36"	1.00"	1450	50000	5000	Natural Light
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	220	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PLL7TMUQ9WVL DLC Search	Yes
UL or ETL Listed		UL Classification				Warranty	
Yes		cULus - Damp Location Rated				5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051