

S39391

22W/LED/HID/5000K/100-277V/E26 22 watt LED HID Replacement; 5000K; Medium base; 100-277

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 2.5KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
8.5 inch	6 inch	6 inch						

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 600V) 92-410



S39391

HID Eq	uivalen	nt Bas	: A	NSI ase	Lamp	Code		Dimmable/ Dimmab	Fi	nish	MOL In Inches	MOD In Inches
100	WC	Medi	um E	E26 22W/	LED/HID/500	0K/10	00-277V/E26	Non-Dimm	able W	/hite	5-11/16"	2-3/8"
Initia Lume		Average Hou		Kelvin Temp	Color	CRI	Beam Spread Deg	Burning	Position	Оре	erating Te	emperature
308	80	500	000	5000	Natural Light	80	300	Up, Down, or Horizontal Operation Only		-20C (-4F) to a maximum of +65C (+149F)		
Pack		kage ype	CE	C Status	Material		RoHS Compliant	UL or ETL Listed	UL Clas	ssificati	ion	Warranty
48	В	Вох		l for sale in alifornia	Aluminum	1	Yes	Yes	cULus - Da	amp Loo ated	cation 5	Year Limited

50/60Hz



S39391

Hi-Pro

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

045923303913

100 - 277

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



40W

@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051

150W