

S39392

36W/LED/HID/5000K/100-277V/E26 36 watt LED HID Replacement; 5000K; Medium base; 100-277

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size									
Length	Width	Depth							
8.5 inch	6 inch	6 inch							

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 600V) 92-410



S39392

HID Eq	uivalent	t Bas	e	NSI ase		Lamp	Code		Dimmable/ Dimmab		Finish	MOL I Inche	
150	0W	Medium E26 36W/LED/HID/5000K/100-277V/E		0-277V/E26	Non-Dimm	able	White	7-11/3	2" 3-11/32"				
Initia Lume		Average Hou		Kelvi Tem		Color	CRI	Beam Spread Deg	Burning	Position	C	perating	Temperature
5148 50000		000	500	0	Natural Light	80	300	Up, Down, or Horizontal Operation Only		n -20	-20C (-4F) to a maximum of +65C (+149F)		
Pack		nckage CEC Status		S	Material RoHS Compliant			UL or ETL Listed	UL Classification		Warranty		
12	В	ox Lawful for sale in California			Aluminum Yes		Yes	Yes	cULus - Damp Location Rated		5 Year Limited		

50/60Hz

100 - 277



S39392

Hi-Pro

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

045923303920

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



55W

@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051

200W