

S39393

45W/LED/HID/5000K/100-277V/EX39 45 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
 UL approved for totally enclosed fixtures
 Damp location IP64 rated

- For outdoor & indoor use
- Base up, base down or horizontal operation
- High-bay / Low-bay / Post-top
 Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size								
Length	Width	Depth						
8 inch	8 inch	11 inch						

Optional Accessories

In-line surge protector <u>80-929</u>



S39393

Item	Product	UPC	Input	Watts	Operating	Incandescent	Fluorescent
Number	Line		Voltage		Frequency	Equivalent	Equivalent

S393	393	Hi-F	Pro 0	459233	303937	100 - 2	77	45	50	0/60Hz 30		300W	0W		65W	
	ID valent		Base	ANSI Base		Lamp Code					nable/Non- Fi mmable		inish	MOL In Inches	MOD In Inches	
17	5W		Vlogul ktended	EX39	3 4	45W/LED/HID/5000K/100- 277V/EX39)-	Non-E	Dimmable White		/hite	8-13/16"	3-11/32"	
Init Lum			ige Rated Hours	Kelv Ter		Color CRI Beam Spread Deg		Burni	Burning Position			Operating Temperature				
64	35	5	50000	500	00	latural Light	80	0 300 Up, Down, or O O Only		on	-20C (-4F) to a maximum of +65C (+149F)					
Pack	Pack Typ	CEC Status		DL	C ID:	Matarial			oHS UL or npliant ETL l Listed		UL	UL Classification		Warranty		
12	Bo	X	Lawful for sale L271RHFVSJ\ in California DLC Search			Alu	Numinum		Yes	Yes	cULus - Da Location R			<u>5 Year</u> Limited		



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051