

BLOWER WHEELS

Single Inlet, Galvanized



Manufactured for OEM Applications



- **Can be bored to fit odd or larger sizes up to 5/8"**
- **Use for packaged terminal air conditioners (PTAC) systems, room air conditioners, fan coil units, draft inducers, power burners and heaters**
- **Can combine two to replace double inlet wheels**
(see Technical Tip on Page 43)

SINGLE INLET GALVANIZED

Lau Part Number	Max. RPM	Dia.	Width	Rot.	Bore Size	OEM Applications
02895768	4500	3 ¹³ / ₁₆ "	1 ⁷ / ₈ "	CW	5/ ₁₆ "	Draft Inducers, Evcon
02895769	4500	3 ¹³ / ₁₆ "	1 ⁷ / ₈ "	CCW	5/ ₁₆ "	Draft Inducers
02895770	4500	3 ¹³ / ₁₆ "	2 ¹ / ₂ "	CW	5/ ₁₆ "	Draft Inducers, Reznor
02895771	4500	3 ¹³ / ₁₆ "	2 ¹ / ₂ "	CCW	5/ ₁₆ "	Draft Inducers, Reznor
02895772	4500	3 ²⁷ / ₃₂ "	1 ¹ / ₄ "	CW	1/ ₄ "	Carrier, Draft Inducers
02895773	4500	3 ²⁷ / ₃₂ "	1 ¹ / ₄ "	CCW	1/ ₄ "	Carrier, Draft Inducers
02895721	4500	4 1/4"	2 1/2"	CW	3/ ₈ "	
02895722	4500	4 1/4"	2 1/2"	CCW	3/ ₈ "	
02895725	3450	4 3/4"	2 1/16"	CW	1/ ₂ "	
02895726	3450	4 3/4"	2 1/16"	CCW	1/ ₂ "	
02895727	3450	4 3/4"	2 1/2"	CW	1/ ₂ "	
02895728	3450	4 3/4"	2 1/2"	CCW	1/ ₂ "	
02895729	3450	4 3/4"	2 15/16"	CW	1/ ₂ "	
02895730	3450	4 3/4"	2 15/16"	CCW	1/ ₂ "	
02895731	3450	4 3/4"	3 7/16"	CW	1/ ₂ "	
02895732	3450	4 3/4"	3 7/16"	CCW	1/ ₂ "	
02895733	3450	5 1/4"	2 1/16"	CW	1/ ₂ "	
02895734	3450	5 1/4"	2 1/16"	CCW	1/ ₂ "	
02895735	3450	5 1/4"	2 1/2"	CW	1/ ₂ "	Carrier
02895736	3450	5 1/4"	2 1/2"	CCW	1/ ₂ "	Carrier

Maximum Operating Temperature, 200°F.

Continued on next page



BLOWER WHEELS

Single Inlet, Galvanized

Manufactured for OEM Applications

SINGLE INLET GALVANIZED

Lau Part Number	Max. RPM	Dia.	Width	Rot.	Bore Size	OEM Applications
02895737	3450	5 $\frac{1}{4}$ "	2 $\frac{15}{16}$ "	CW	$\frac{1}{2}$ "	
02895738	3450	5 $\frac{1}{4}$ "	2 $\frac{15}{16}$ "	CCW	$\frac{1}{2}$ "	
02895739	3450	5 $\frac{1}{4}$ "	3 $\frac{7}{16}$ "	CW	$\frac{1}{2}$ "	
02895740	5700	5 $\frac{1}{4}$ "	3 $\frac{7}{16}$ "	CCW	$\frac{1}{2}$ "	
02895753	3450	5 $\frac{3}{4}$ "	2 $\frac{1}{16}$ "	CW	$\frac{1}{2}$ "	
02895754	3450	5 $\frac{3}{4}$ "	2 $\frac{1}{16}$ "	CCW	$\frac{1}{2}$ "	
02895755	3450	5 $\frac{3}{4}$ "	2 $\frac{1}{2}$ "	CW	$\frac{1}{2}$ "	
02895756	3450	5 $\frac{3}{4}$ "	2 $\frac{1}{2}$ "	CCW	$\frac{1}{2}$ "	
02895757	3450	5 $\frac{3}{4}$ "	2 $\frac{15}{16}$ "	CW	$\frac{1}{2}$ "	
02895758	3450	5 $\frac{3}{4}$ "	2 $\frac{15}{16}$ "	CCW	$\frac{1}{2}$ "	
02895759	3450	5 $\frac{3}{4}$ "	3 $\frac{7}{16}$ "	CW	$\frac{1}{2}$ "	Friedrich
02895760	3450	5 $\frac{3}{4}$ "	3 $\frac{7}{16}$ "	CCW	$\frac{1}{2}$ "	
02895761	3450	5 $\frac{3}{4}$ "	3 $\frac{13}{16}$ "	CW	$\frac{1}{2}$ "	
02895762	3450	5 $\frac{3}{4}$ "	3 $\frac{13}{16}$ "	CCW	$\frac{1}{2}$ "	
02895779	2800	5 $\frac{3}{4}$ "	4"	CW	$\frac{1}{2}$ "	
02895780	2800	5 $\frac{3}{4}$ "	4"	CCW	$\frac{1}{2}$ "	
02895781	3450	6 $\frac{1}{4}$ "	4"	CW	$\frac{1}{2}$ "	
02895782	3450	6 $\frac{1}{4}$ "	4"	CCW	$\frac{1}{2}$ "	
02895751	3450	6 $\frac{1}{4}$ "	4 $\frac{1}{4}$ "	CW	$\frac{1}{2}$ "	
02895752	3450	6 $\frac{1}{4}$ "	4 $\frac{1}{4}$ "	CCW	$\frac{1}{2}$ "	
02895741	3450	6 $\frac{5}{16}$ "	2 $\frac{1}{16}$ "	CW	$\frac{1}{2}$ "	
02895742	3450	6 $\frac{5}{16}$ "	2 $\frac{1}{16}$ "	CCW	$\frac{1}{2}$ "	
02895743	3450	6 $\frac{5}{16}$ "	2 $\frac{1}{2}$ "	CW	$\frac{1}{2}$ "	
02895744	3450	6 $\frac{5}{16}$ "	2 $\frac{1}{2}$ "	CCW	$\frac{1}{2}$ "	
02895745	3450	6 $\frac{5}{16}$ "	2 $\frac{15}{16}$ "	CW	$\frac{1}{2}$ "	
02895746	3450	6 $\frac{5}{16}$ "	2 $\frac{15}{16}$ "	CCW	$\frac{1}{2}$ "	
02895747	3450	6 $\frac{5}{16}$ "	3 $\frac{7}{16}$ "	CW	$\frac{1}{2}$ "	
02895748	3450	6 $\frac{5}{16}$ "	3 $\frac{7}{16}$ "	CCW	$\frac{1}{2}$ "	
02895749	3450	6 $\frac{5}{16}$ "	3 $\frac{13}{16}$ "	CW	$\frac{1}{2}$ "	
02895750	3450	6 $\frac{5}{16}$ "	3 $\frac{13}{16}$ "	CCW	$\frac{1}{2}$ "	
02049153	4000	7 $\frac{3}{32}$ "	3 $\frac{5}{32}$ "	CW	$\frac{1}{2}$ "	
02049154	4000	7 $\frac{3}{32}$ "	3 $\frac{5}{32}$ "	CCW	$\frac{1}{2}$ "	

Maximum Operating Temperature, 200°F.

Continued on next page

Specifications are subject to change without notice or obligation

BLOWER WHEELS

Single Inlet, Galvanized



Manufactured for OEM Applications

SINGLE INLET GALVANIZED

Lau Part Number	Max. RPM	Dia.	Width	Rot.	Bore Size	OEM Applications
02049115	2500	7 ⁷ / ₁₆ "	2 ¹ / ₂ "	CW	1/2"	
02049142	2500	7 ⁷ / ₁₆ "	2 ¹ / ₂ "	CCW	1/2"	
02049124	1650	7 ⁷ / ₁₆ "	2 ³ / ₄ "	CW	1/2"	
02049125	1650	7 ⁷ / ₁₆ "	2 ³ / ₄ "	CCW	1/2"	
02049137	1650	7 ⁷ / ₁₆ "	3 ¹ / ₂ "	CW	1/2"	
02049120	1650	7 ⁷ / ₁₆ "	3 ¹ / ₂ "	CCW	1/2"	
02049161	2000	7 ¹ / ₂ "	2 ³ / ₄ "	CW	1/2"	
02049162	2000	7 ¹ / ₂ "	2 ³ / ₄ "	CCW	1/2"	
02049163	4000	7 ¹ / ₂ "	3 ⁵ / ₃₂ "	CW	1/2"	
02049164	4000	7 ¹ / ₂ "	3 ⁵ / ₃₂ "	CCW	1/2"	
02049165	3000	7 ¹ / ₂ "	4"	CW	1/2"	Carrier
02049166	3000	7 ¹ / ₂ "	4"	CCW	1/2"	Carrier
02048765	3000	8"	4"	CW	1/2"	
02048766	3000	8"	4"	CCW	1/2"	
02048768	4000	8 ¹ / ₂ "	3 ³ / ₁₆ "	CCW	1/2"	
02048705	1650	8 ¹ / ₂ "	4"	CW	1/2"	
02048706	1650	8 ¹ / ₂ "	4"	CCW	1/2"	
02048769	3000	8 ¹ / ₂ "	4"	CW	1/2"	
02048771	1400	8 ¹ / ₂ "	4 ¹ / ₄ "	CW	1/2"	
02048772	1750	8 ¹ / ₂ "	4 ¹ / ₄ "	CCW	1/2"	
02048738	1750	8 ¹ / ₂ "	4 ¹ / ₂ "	CW	1/2"	
02048739	1750	8 ¹ / ₂ "	4 ¹ / ₂ "	CCW	1/2"	
02055301	1750	9 ¹ / ₈ "	3 ³ / ₄ "	CW	1/2"	
02055303	1750	9 ¹ / ₈ "	3 ³ / ₄ "	CCW	1/2"	
02055302	1750	9 ¹ / ₈ "	4 ¹ / ₄ "	CW	1/2"	Carrier
02055304	1750	9 ¹ / ₈ "	4 ¹ / ₄ "	CCW	1/2"	Carrier
01351110	1750	9 ¹⁵ / ₁₆ "	6"	CCW	5/8"	Fedders

Maximum Operating Temperature, 200°F.

Specifications are subject to change without notice or obligation