



AIR CONDITIONER

18,000 BTU WINDOW AC




FOLLOW ME
Portable remote control
thermostat feature for
total room coverage

CHOOSING

THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM


1 MEASURE AREA OF THE ROOM



2 MATCH ROOM SIZE WITH CORRECT BTUs


ROOM SIZE (sq. ft.)		BTUs
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500

3 CONFIRM WINDOW OPENING SIZE



4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS



DETERMINE IF YOUR CIRCUIT IS ADEQUATE

WINDOW AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24-hour timer
- Window mounting kit
- Auto restart function
- Tilt-out filter access

	4PAC18000
UPC CODE	8-42149-02552-6
COOLING CAPACITY (BTU)	18,000
COVERAGE (sq. ft.)	700–1,000
EER	11.8
ENERGY STAR RATED	Yes
FAN SPEEDS (Cool/Fan)	3/3
AMPS	7.5
WATTS	1,525/1,500
DECIBELS (Hi/Mi/Lo)	60/57/54
WINDOW WIDTH (Min./Max.) (in.)	28/40 ^{1/2}
WINDOW HEIGHT (Min.) (in.)	18 ^{1/2}
UNIT DIMENSIONS (WxHxD) (in.)	23 ^{3/4} x 18 x 25 ^{1/2}
PKG. DIMENSIONS (WxHxD) (in.)	25 ^{3/4} x 19 ^{3/4} x 29 ^{1/2}
STUFFING QTY. (20'/40'/40' HQ)	96/216/270
WEIGHT (Net/Gross) (lbs.)	114/132
REFRIGERATION	R410A
OUTLET CONFIGURATION	15 AMP 230V



PA/SS_4PAC18000/05022019

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us