

Baseboard Heater

Slim contoured design is the perfect complement to both contemporary and traditional décors.

Features

- Exclusive contoured design with safe rounded endcaps and attractive styling
- May be used with wall, or unique side mounted built-in thermostat (not included)
- Superior finned tubular element design for safety and long life
- Large rear-entry junction boxes on both sides for quick and easy installation
- Full-length automatic reset overheat protection for safety

Applications

- All residential applications, commercial offices, washrooms, lobbies



Unique side mount optional thermostat may be installed from the rear without removing front panel.

Specifications

Voltage	120, 208, 240, 277, 347, 600V
Wattage	Sizes ranging from 300W to 2500W
Colour	White or Almond
Finish	Specially-formulated epoxy / polyester powder coating is environmentally friendly and resists fading and abrasion.
Heating Element	A nickel chromium element is totally enclosed within a stainless steel sheath providing superior life expectancy and resistance to rust. Aluminum fins are firmly staked to the surface to provide excellent heat transfer.
Installation	Large rear entry left and right junction boxes provide ease of installation.
Warranty	Ten year element warranty. One year warranty on complete unit. CSA certified and UL approved.



Control Options (field installed)

Thermostat Kits

Cat. No.	Description	Rating
DTK-SP	Single pole built-in thermostat kit (adjustable)	120-240V, 17A, 347V, 14A, 600V, 10A
DTK-DP	Double pole built-in thermostat (adjustable)	120-240V, 17A, 347V, 11A, 600V, 10A
DTKT-SP	Single pole built-in tamperproof thermostat kit	120-240V, 17A, 347V, 11A
DTKT-DP	Double pole built-in tamperproof thermostat kit	120-240V, 25A, 347V, 11A, 600V, 10A

Note: Each adjustable kit contains white and almond control knobs and hardware

Relays

Cat. No.	Description	Rating
BLLVC11	Low voltage relay & transformer kit	120V, 22A
BLLVC21	Low voltage relay & transformer kit	208V, 22A
BLLVC31	Low voltage relay & transformer kit	240V, 22A
BLLVC41	Low voltage relay & transformer kit	277V, 22A
BLLVC51	Low voltage relay & transformer kit	347V, 17A
BLLVC81	Low voltage relay & transformer kit	600V, 10A

Relays

Cat. No.	Description	Rating
BLLVD	Low voltage relay less transformer kit	120/208/240, 22A, 347V, 17A, 600V, 10A
BUS2	Disconnect switch, double pole	277V, 25A

Inside Corners

Cat. No.	Description
BNIC	Almond
BNICW	White

Note: Inside corners are used when continuous installation of baseboard cabinetry inside 90 degree corners is designed.

Ordering Guide

Cat. No.	Watts	BTU	Volts	Length (mm/in.)	Weight (kg/lbs.)
BN2203W11	300	1024	120	560/22 1/8	2.3/5
BN2203W21	300	1024	208	560/22 1/8	2.3/5
BN2203W31	300/225	1024/768	240/208	560/22 1/8	2.3/5
BN2203W41	300	1024	277	560/22 1/8	2.3/5
BN2805W11	500	1706	120	700/27 5/8	2.7/6
BN2805W21	500	1706	208	700/27 5/8	2.7/6
BN2805W31	500/375	1706/1280	240/208	700/27 5/8	2.7/6
BN2805W41	500/375	1706/1280	277/240	700/27 5/8	2.7/6
BN2805W51	500	1706	347	700/27 5/8	2.7/6
BN3907W11	750	2559	120	980/38 5/8	4.1/9
BN3907W21	750	2559	208	980/38 5/8	4.1/9
BN3907W31	750/563	2559/1919	240/208	980/38 5/8	4.1/9
BN3907W41	750/563	2559/1919	277/240	980/38 5/8	4.1/9
BN3907W51	750	2559	347	980/38 5/8	4.1/9
BN3907W81	750	2559	600	980/38 5/8	4.1/9
BN4810W11	1000	3412	120	1210/47 5/8	4.5/10
BN4810W21	1000	3412	208	1210/47 5/8	4.5/10
BN4810W31	1000/750	3412/2559	240/208	1210/47 5/8	4.5/10
BN4810W41	1000/750	3412/2559	277/240	1210/47 5/8	4.5/10
BN4810W51	1000	3412	347	1210/47 5/8	4.5/10
BN4810W81	1000	3412	600	1210/47 5/8	4.5/10
BN5712W11	1250	4265	120	1440/56 11/16	5.4/12
BN5712W21	1250	4265	208	1440/56 11/16	5.4/12
BN5712W31	1250/938	4265/3199	240/208	1440/56 11/16	5.4/12
BN5712W41	1250/938	4265/3199	277/240	1440/56 11/16	5.4/12
BN5712W51	1250	4265	347	1440/56 11/16	5.4/12
BN5712W81	1250	4265	600	1440/56 11/16	5.4/12
BN6615W11	1500	5118	120	1670/65 3/4	5.9/13

Cat. No.	Watts	BTU	Volts	Length (mm/in.)	Weight (kg/lbs.)
BN6615W21	1500	5118	208	1670/65 3/4	5.9/13
BN6615W31	1500/1125	5118/3839	240/208	1670/65 3/4	5.9/13
BN6615W41	1500/1125	5118/3839	277/240	1670/65 3/4	5.9/13
BN6615W51	1500	5118	347	1670/65 3/4	5.9/13
BN6615W81	1500	5118	600	1670/65 3/4	5.9/13
BN7517W21	1750	5971	208	1900/74 3/4	7.3/16
BN7517W31	1750/1313	5971/4478	240/208	1900/74 3/4	7.3/16
BN7517W41	1750/1313	5971/4478	277/240	1900/74 3/4	7.3/16
BN7517W51	1750	5971	347	1900/74 3/4	7.3/16
BN7517W81	1750	5971	600	1900/74 3/4	7.3/16
BN8420W21	2000	6824	208	2130/83 7/8	7.7/17
BN8420W31	2000/1500	6824/5120	240/208	2130/83 7/8	7.7/17
BN8420W41	2000/1500	6824/5120	277/240	2130/83 7/8	7.7/17
BN8420W51	2000	6824	347	2130/83 7/8	7.7/17
BN8420W81	2000	6824	600	2130/83 7/8	7.7/17
BN9322W21	2250	7677	208	2360/92 7/8	8.6/19
BN9322W31	2250/1688	7677/5758	240/208	2360/92 7/8	8.6/19
BN9322W41	2250/1688	7677/5758	277/240	2360/92 7/8	8.6/19
BN9322W51	2250	7677	347	2360/92 7/8	8.6/19
BN9322W81	2250	7677	600	2360/92 7/8	8.6/19
BN10225W21	2500	8530	208	2590/102	9.1/20
BN10225W31	2500/1875	8530/6398	240/208	2590/102	9.1/20
BN10225W41	2500/1875	8530/6398	277/240	2590/102	9.1/20
BN10225W51	2500	8530	347	2590/102	9.1/20
BN10225W81	2500	8530	600	2590/102	9.1/20

Note: 1) Standard colour is White.

2) To order Almond omit "W" in Cat. No.

Dimensions

