

A19 Energy Saver



A19

Order code	Description	Watts (W)	Base	Volts (V)	Lumens output (lm)	Average life (hrs)	Finish	Operating position	Incan. equivalent (W)	Case qty (master)
A19										
62794 ¹	H29/A19/CL/120V/STD	29	E26	120	400	1 000	Clear	Universal	40	100
62795 ¹	H43/A19/CL/120V/STD	43	E26	120	750	1 000	Clear	Universal	60	100
62796 ¹	H53/A19/CL/120V/STD	53	E26	120	1 050	1 000	Clear	Universal	75	100
62799 ¹	H43/A19/FR/120V/STD	43	E26	120	750	1 000	Frost	Universal	60	100
62800 ¹	H53/A19/FR/120V/STD	53	E26	120	1 050	1 000	Frost	Universal	75	100
62801 ¹	H72/A19/FR/120V/STD	72	E26	120	1 490	1 000	Frost	Universal	100	100

JC



JC (G4)



T3 (BA15d)



T3 (E11)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Case qty (inner/master)
JC (G4)								
51129	H10JC/CL/2M/G4/12V/STD	10	G4	12	130	2 000	Clear	100/1 000
51130	H20JC/CL/2M/G4/12V/STD	20	G4	12	300	2 000	Clear	100/1 000
T3 (BA15d)								
50881	H75T3/CL/2M/BA15D/130V/STD	75	BA15d	130	1 120	2 000	Clear	12/120
50950	H100T3/CL/2M/BA15D/130V/STD	100	BA15d	130	1 600	2 000	Clear	12/120
50883	H150T3/CL/2M/BA15D/130V/STD	150	BA15d	130	3 000	2 000	Clear	12/120
50885	H250T3/CL/2M/BA15D/130V/STD	250	BA15d	130	4 800	2 000	Clear	12/120
T3 (E11)								
55028	H50T3/CL/2M/E11/130V/STD	50	E11	130	1 120	2 000	Clear	12/120
50880	H75T3/CL/2M/E11/130V/STD	75	E11	130	1 350	2 000	Clear	12/120
50882	H100T3/CL/2M/E11/130V/STD	100	E11	130	1 800	2 000	Clear	12/120
50951	H150T3/CL/2M/E11/130V/STD	150	E11	130	3 000	2 000	Clear	12/120
50884	H250T3/CL/2M/E11/130V/STD	250	E11	130	4 800	2 000	Clear	12/120

¹This product is affected by provincial Energy Efficiency Regulations in Ontario, Quebec & British Columbia. Note that it will remain available until stock is depleted.



Xenon JD



MOL: 2 15/32 in. (63 mm)
Ø 23/32 in. (18 mm)

T3 (BA15d)



MOL: 2 1/4 in. (57 mm)
Ø 23/32 in. (18 mm)

T3 (E11)



MOL: 2 5/16 in. (59 mm)
Ø 23/32 in. (18 mm)

T3 (E12)



MOL: 1 25/32 in. (45 mm)
Ø 23/32 in. (18 mm)

T3 (E12)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Case qty (inner/master)
T3 (BA15d)								
60956	X60T3/2M/BA15D/120V/STD	60	BA15d	120	960	2 000	Clear	12/120
T3 (E11)								
60950	X40T3/2M/E11/120V/STD	40	E11	120	560	2 000	Clear	12/120
60954	X60T3/2M/E11/120V/STD	60	E11	120	960	2 000	Clear	12/120
T3 (E12)								
60948	X20T3/2M/E12/120V/STD	20	E12	120	200	2 000	Clear	12/120
T3 (E12)								
60949	X20T3/F/2M/E12/120V/STD	20	E12	120	200	2 000	Frost	12/120
60953	X40T3/F/2M/E12/120V/STD	40	E12	120	560	2 000	Frost	12/120



JD & JCD



MOL: 1 21/32 in. (42 mm)
Ø 15/32 in. (12 mm)

JD (G9 Glass Base)



MOL: 2 7/32 in. (56 mm)
Ø 15/32 in. (12 mm)

JD (G9 Ceramic Base)



MOL: 1 13/16 in. (46 mm)
Ø 1/2 in. (13 mm)

JCD (GY6.35)



MOL: 1 13/16 in. (46 mm)
Ø 1/2 in. (13 mm)

JCD (G8)



MOL: 1 7/8 in. (47.5 mm)
Ø 1/2 in. (13 mm)

JCD (GY8)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Case qty (inner/master)
JD (G9) - Glass Base								
58260	H25JD/42mm/CL/2M/G9/130V/STD	25	G9	130	255	2 000	Clear	12/120
57259	H40JD/42MM/CL/2M/G9/130V/STD	40	G9	130	480	2 000	Clear	12/120
57256	H40JD/42MM/F/2M/G9/130V/STD	40	G9	130	480	2 000	Frost	12/120
57255	H50JD/42MM/CL/2M/G9/130V/STD	50	G9	130	600	2 000	Clear	12/120
57258	H60JD/42MM/CL/2M/G9/130V/STD	60	G9	130	800	2 000	Clear	12/120
58258	H75JD/42mm/CL/2M/G9/130V/STD	75	G9	130	1 050	2 000	Clear	12/120
JD (G9) - Ceramic Base								
55057	H25JD/56MM/CL/2M/G9/120V/STD	25	G9	120	255	2 000	Clear	12/120
55058	H40JD/56MM/CL/2M/G9/120V/STD	40	G9	120	480	2 000	Clear	12/120
11247	H50JD/56MM/CL/2M/G9/120V/STD	50	G9	120	600	2 000	Clear	12/120
55060	H75JD/56MM/CL/2M/G9/120V/STD	75	G9	120	1 050	2 000	Clear	12/120
JCD (GY6.35)								
51045	H20JCD/CL/2M/GY6.35/120V/STD	20	GY6.35	120	180	2 000	Clear	12/120
50879	H35JCD/CL/2M/GY6.35/120V/STD	35	GY6.35	120	380	2 000	Clear	12/120
50878	H50JCD/CL/2M/GY6.35/120V/STD	50	GY6.35	120	600	2 000	Clear	12/120
10317	H75JCD/CL/2M/GY6.35/120V/STD	75	GY6.35	120	1 050	2 000	Clear	12/120
JCD (G8)								
55055	H20JCD/CL/2M/G8/120V/STD	20	G8	120	200	2 000	Clear	12/120
15710	JCD100W/130V/G8	100	G8	130	1 600	2 000	Clear	12/120
JCD (GY8)								
11267	H75JCD/CL/2M/GY8/120V	75	GY8	120	1 300	2 000	Clear	10/50



J Type Double Ended



T3 - 79 mm



T3 - 119 mm



T3 - 256 mm

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Case qty (inner/master)
T3 - 79 mm								
68200	H60T3/79mm/CL/2M/R7S/130V/STD	60	R7s	130	800	2 000	Clear	12/120
57225	H75T3/79mm/2M/R7S/120V/STD	75	R7s	120	750	2 000	Clear	12/480
55047	H75T3/79mm/CL/2M/R7S/130V/JPN/STD	75	R7s	130	1 150	2 000	Clear	12/480
57361	H100T3/79mm/2M/R7S/120V/STD	100	R7s	120	1 300	2 000	Clear	12/120
51043	H100T3/79mm/2M/R7S/130V/STD	100	R7s	130	1 300	2 000	Clear	12/120
57224	H150T3/79mm/2M/R7S/120V/STD	150	R7s	120	2 400	2 000	Clear	12/120
51075	H150T3/79mm/2M/R7S/130V/STD	150	R7s	130	2 400	2 000	Clear	12/120
51120	H200T3/79mm/2M/R7S/130V/STD	200	R7s	130	3 400	2 000	Clear	12/120
T3 - 119 mm								
51086	H100T3/119mm/2M/R7S/130V/STD	100	R7s	130	1 300	2 000	Clear	12/120
50903	H150T3/119mm/2M/R7S/130V/STD	150	R7s	130	1 800	2 000	Clear	12/120
51044	H200T3/119mm/2M/R7S/130V/STD	200	R7s	130	3 400	2 000	Clear	12/120
51078	H300T3/119mm/CL/2M/R7S/120V/STD	300	R7s	120	5 950	2 000	Clear	12/120
51041	H300T3/119mm/CL/2M/R7S/130V/STD	300	R7s	130	5 950	2 000	Clear	12/120
51076	H500T3/119mm/CL/2M/R7S/120V/STD	500	R7s	120	10 500	2 000	Clear	12/120
51077	H500T3/119mm/CL/2M/R7S/130V/STD	500	R7s	130	10 500	2 000	Clear	12/120
T3 - 190 mm								
51046	H1000T3/190mm/CL/2M/R7S/130V/STD	1 000	R7s	130	21 000	2 000	Clear	12/120
T3 - High Voltage								
59261	H300QT3/119mm/CL/2M/220V/STD	300	R7s	220	33 000	2 000	Clear	12/120
51047	H1000T3/190mm/CL/2M/R7S/240V/STD	1 000	R7s	240	21 000	2 000	Clear	12/120
51085	H1000T3/256mm/CL/2M/R7S/240V/STD	1 000	R7s	240	21 000	2 000	Clear	12/120
59262	H1500QT3/256mm/CL/2M/R7S/208V/STD	1 500	R7s	208	33 000	2 000	Clear	12/120
51049	H1500T3/256mm/CL/2M/R7S/240V/STD	1 500	R7s	240	26 400	2 000	Clear	12/120
59260	H1500QT3/256mm/CL/2M/277V/STD	1 500	R7s	277	33 000	2 000	Clear	12/120
T3 - Low Voltage								
55088	H150T3/79mm/2M/R7S/12V/STD	150	R7s	12	2 900	2 000	Clear	10/100
10318	H300T3/119mm/CL/2M/R7S/24V/STD	300	R7s	24	5 400	2 000	Clear	10/100
10319	H300T3/119mm/CL/2M/R7S/32V/STD	300	R7s	32	5 400	2 000	Clear	10/100
T3 - Infrared								
55077	H375T3/221mm/CL/IR/5M/R7S/120V/STD	375	R7s	120	N/A	5 000	Clear	1/84
55070	H500T3/221mm/CL/IR/5M/R7S/120V/STD	500	R7s	120	N/A	5 000	Clear	1/25
55072	H1000T3/351mm/CL/IR/5M/ML/240V/STD	1 000	Metal Leads	240	N/A	5 000	Clear	1/25
55074	H1600T3/503mm/CL/IR/5M/ML/240V/STD	1 600	Metal Leads	240	N/A	5 000	Clear	1/25
55076	H3800T3/1062mm/CL/IR/5M/ML/570V/STD	3 800	Metal Leads	570	N/A	5 000	Clear	1/25

