



LED Outdoor Luminaires



STANDARD™



Solutions that are Illuminating

Versatility

STANDARD's LED outdoor luminaires offer flexibility in mounting options and design. Perfect for outfitting any traditional luminaires, including HID (HM, HSP) and halogen luminaires

Testing

With constant technological innovations in the world of LEDs, it is increasingly important that all LED components are properly tested and qualified. STANDARD takes great precaution to ensure all LED luminaires complete rigorous testing procedures in order to guarantee the highest levels of quality. LM79, LM80 and tight binning processes ensure uniformity in light output and colour from luminaire to luminaire.



Installation Flexibility

With a variety of mounting options and simple, easy installation methods, for wall, flood and area applications, these luminaires ensure quick and seamless upgrades in any scenario.

Durability

These commercial grade LED outdoor luminaires boast durability in their robust die-cast construction and powder coat finish ensuring resistance to both cold and UV damage. With starting temperatures as low as -30 °C, even the drivers are protected in the coldest of temperatures. Rigorous salt spray and scratch testing ensure protection against corrosion.

Superior Performance

Boasting an extensive lumen package range using high quality, long life LED chips, these luminaires ensure significant energy savings while minimizing maintenance costs at the same time.



STANDARD's LED Wall Pack luminaires are ideal replacements for traditional High Pressure Sodium and Metal Halide fixtures, while offering a similar design with significant reduction in energy and maintenance costs.

- ▶ Bronze die cast aluminum heat sink
- ▶ Exceptional performance in cold climates, operating temperature: -30 °C / -22°F to 40 °C/ 104°F
- ▶ Integrated dusk to dawn photocell included with the Wall Pack Round Series luminaires
- ▶ Classic Wall Packs use corrosion resistant stainless steel bolts and screws
- ▶ Shield available for Classic Wall Packs to minimize up light
- ▶ 2kV surge protection included

Wall Pack Round



Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)
Wall Pack Round								
63318*	LED/WP/22W/40K/120-277V/PC/STD	22	120-277	4 000	>70	50 000	1 300	180
63319*	LED/WP/30W/40K/120-277V/PC/STD	30	120-277	4 000	>70	50 000	1 900	180

Wall Pack Classic



Shield



Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)
Wall Pack Classic								
63321	LED/WP/60W/40K/120-277V/STD	60	120-277	4 000	>70	50 000	5 000	120
63322	LED/WP/80W/40K/120-277V/STD	80	120-277	4 000	>70	50 000	7 200	120

Order code	Description	Mounting type
------------	-------------	---------------

Mounting Accessories

63593 LED/SHIELD/WPCCLASS/STD

Shield

*: NON-DLC



Wall Pack Series

STANDARD's Universal Slim Series luminaires offer a sleek design with adjustable positioning to ensure light is being directed in the right locations.

- ▶ Bronze die cast aluminum heat sink
- ▶ Exceptional performance in cold climates, operating temperature: -30 °C / -22°F to 40 °C/ 104°F
- ▶ Variety of commercial grade mounting options allow for versatility in wall and flood applications – including mounting directly to masonry and 3 ½" to 4" octagonal and square junction boxes
- ▶ 2kV surge protection included
- ▶ Trunnion mounting option allows for easy conversion from wall mount to flood light luminaire

Perfect for lighting entrances, walkways and perimeter of buildings.



Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)
Universal SLIM								
63314	LED/WP/SLM/20W/40K/120-277V/STD	20	120-277	4 000	>70	50 000	1 850	140
63315	LED/WP/SLM/30W/40K/120-277V/STD	30	120-277	4 000	>70	50 000	2 650	140
63316	LED/WP/SLM/50W/40K/120-277V/STD	50	120-277	4 000	>70	50 000	4 100	140
63317	LED/WP/SLM/80W/40K/120-277V/STD	80	120-277	4 000	>70	50 000	6 900	140



Universal SLIM Series



Extension Arm



Slip Fitter



Trunion / Yoke



Knuckle

Order code	Description	Mounting type	Compatible with
Mounting Accessories			
63347	KN/BACKET/WP/SLIM/STD	KNUCKLE	63314, 63315
63344	EXTARM/BACKET/WP/SLM/STD	EXTENSION ARM	63314, 63315, 63316, 63317
63345	SF/BACKET/WP/SLM/STD	SLIP FITTER	63316, 63317
63346	TR-YK/BACKET/WP/SLM/STD	TRUNNION/ YOKE	63314, 63315

SLIM Series Accessories



Flood light
with knuckle



Flood light
with slip fitter



Flood light
with slip fitter

Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)	Mounting Type
Flood Light									
63323	LED/FL/10W/30K/KN/120-277V/STD	10	120-277	3 000	>70	50 000	900	120	KNUCLE
63324	LED/FL/10W/40K/KN/120-277V/STD	10	120-277	4 000	>70	50 000	900	120	KNUCLE
63325	LED/FL/30W/30K/KN/120-277/STD	30	120-277	3 000	>70	50 000	2 100	120	KNUCLE
63326	LED/FL/30W/40K/KN/120-277/STD	30	120-277	4 000	>70	50 000	2 100	120	KNUCLE
63327	LED/FL/50W/40K/KN/120-277/STD	50	120-277	4 000	>70	50 000	3 700	120	KNUCLE
63328	LED/FL/80W/40K/SF/120-277/STD	80	120-277	4 000	>70	50 000	6 200	120	SLIP FITTER
63329	LED/FL/100W/40K/SF/120-277/STD	100	120-277	4 000	>70	50 000	7 800	120	SLIP FITTER
63337	LED/FL/120W/40K/SF/120-277/STD	120	120-277	4 000	>70	50 000	10 000	120	SLIP FITTER
63338	LED/FL/160W/40K/SF/120-277/STD	160	120-277	4 000	>70	50 000	14 200	120	SLIP FITTER
63339	LED/FL/200W/40K/SF/120-277/STD	200	120-277	4 000	>70	50 000	16 500	120	SLIP FITTER



Flood Light Series



STANDARD's LED Flood and Yard Light Series are designed for use in commercial, difficult to reach areas that typically house traditional energy consuming fixtures. Versatility in mounting options allows for installation in a variety of applications.

- ▶ Bronze die cast aluminum heat sink
- ▶ Exceptional performance in cold climates, operating temperature: -30 °C / -22°F to 40 °C / 104°F
- ▶ Corrosion resistant stainless steel bolts and screws
- ▶ Yard light comes complete with integrated photocell
- ▶ 2kV surge protection included

Perfect for use for wall washing, lighting pathways, signage lighting.



Flood light
with trunnion



Flood light
with yoke



Flood light
with yoke



Yard light

Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)	Mounting Type
63330	LED/FL/30W/40K/YK/120-277/STD	30	120-277	4 000	>70	50 000	2 100	120	YOKE
63331	LED/FL/50W/40K/YK/120-277/STD	50	120-277	4 000	>70	50 000	3 700	120	YOKE
63332	LED/FL/80W/40K/YK/120/277/STD	80	120-277	4 000	>70	50 000	6 200	120	YOKE
63333	LED/FL/100W/40K/YK/120/277/STD	100	120-277	4 000	>70	50 000	7 800	120	YOKE
63334	LED/FL/120W/40K/TM/120-277/STD	120	120-277	4 000	>70	50 000	10 000	120	TRUNNION
63335	LED/FL/160W/40K/TM/120-277/STD	160	120-277	4 000	>70	50 000	14 200	120	TRUNNION
63336	LED/FL/200W/40K/TM/120-277/STD	200	120-277	4 000	>70	50000	16 500	120	TRUNNION

Order code	Description	Watts (W)	Volts (VAC)	Colour Temperature (K)	CRI	Life (L70)	Initial lumens (lm)	Beam angle (°)
------------	-------------	--------------	----------------	---------------------------	-----	---------------	------------------------	-------------------

Yard Light

63340	LED/YL/35W/40K/120-277/STD	35	120-277	4 000	>70	50 000	2 500	120
63341	LED/YL/50W/40K/120-277/STD	50	120-277	4 000	>70	50 000	4 200	120



Yard Light Series

Luminaire LED Outdoor

STANDARD[™]

1-800-361-6965
www.standardpro.com