

Project: \_\_\_\_\_ Type: \_\_\_\_\_  
 Drawn by: \_\_\_\_\_ Catalogue #: \_\_\_\_\_ Date: \_\_\_\_\_

## Individual Spec Sheet

# LED EDGELIT

## LED CEILING LUMINAIRE

8"

### ORDERING INFORMATION

**Order code:** 67371  
**Model number:** LED/CL8/EDGELIT/14W/30K/FM/RND/BN/STD  
**UPC:** 069549673717  
**Case quantity:** 20

### PHYSICAL DATA

**Size in. (mm):** 8 (206)  
**Shape:** Round  
**Type:** Ceiling  
**Trim finish:** Brushed Nickel  
**Lens material:** Frosted Polycarbonate  
**Mounting:** Surface Mount/Flush-mount

### PERFORMANCE DATA

**Watts (W):** 14  
**Volts (VAC):** 120  
**Colour temperature (K)<sup>1</sup>:** 3 000  
**Lumen output (lm)<sup>2</sup>:** 1 214.6  
**Lumen per Watts (lm/W):** 72  
**CRI:** >80  
**Life L70 (h)<sup>3</sup>:** 50 000  
**Beam angle (°):** 120  
**THD (%):** >15  
**Power factor:** 0.95  
**Dimmer type:** Forward-Reverse phase  
**Frequency (Hz):** 60  
**Operating temp. range:** -20 °C to 50 °C (-4 °F to 122 °F)

<sup>1</sup> Typical colour temperature range: +/- 5 %

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

<sup>3</sup> Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

### COMPATIBLE DIMMERS

Brand	Model
COOPER	RRD-6NA-WH, AAL06, SLC03P
LEGRAND	RH703PTUTC
LEVITON	6615, IPL06, 6674, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ, DDMX1
LUTRON	DVCL-153P, CTCL-153P, AYCL-253P, DVRP-253P-WH, SELV-300P

NOTE: The above table shows dimmers that have been tested and have demonstrated proper operation under normal conditions. Each installation being unique, various factors such as load, common neutrals or other electrical products on the circuit can, in certain instances, cause variance in system performance. Read and comply to the dimmer installation instructions. Consult dimming system manufacturer for additional support in operation. Stanpro recommends to use dimmers designed to work with LED products. Older dimmers designed for incandescent products may cause erratic operation. Some dimmers may require more than one product for stable operation. The maximum number of products is determined by the dimmer wattage rating with LEDs. Be careful, these dimmers have different ratings depending on the product type. Again, refer to the dimmer installation instructions.

This lighting equipment complies with Canadian standard ICES-005 for use in residential applications.  
 Data is based upon tests performed in a controlled environment.  
 Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



**5** yrs  
warranty

**quick ship**

**LED fixture**

**dimmmable fixture**


**wet location**



ICES  
005




## DIMENSIONS

PHOTOMETRIC DATA<sup>1</sup>

67371 • LED/CL8/EDGELIT/14W/30K/FM/RND/BN/STD • 1 214.6 lm

## Polar candela distribution

<sup>1</sup> Complete IES files available on our website.

## Zonal lumen summary

Zone	Lumens	% Fixture
0-30	335.6	27.6
0-40	550.7	45.3
0-60	965.7	79.5
60-90	242.6	20
70-100	99.1	8.2
90-120	2.2	0.2
0-90	1 208.3	99.5
90-180	6.3	0.5
0-180	1 214.6	100

## Illuminance at a distance

	Center beam fc	Beam width
17.0'	1.48	49.6' 49.5'
34.0'	0.37	99.1' 99.0'
51.0'	0.16	148.7' 148.4'
68.0'	0.09	198.2' 197.9'
85.0'	0.06	247.8' 247.4'
102.0'	0.04	297.3' 296.9'

■ Vert. spread: 111.1°  
■ Horiz. spread: 111.0°

Qty	Description	Price

I accept the specifications of the luminaire configuration mentioned above.

Name: \_\_\_\_\_

Company: \_\_\_\_\_

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions.  
All products are subject to change or may be discontinued any time without notice.