



WHITE OUT (SURFACE SEALER)

#16-053 White

A stain killing primer that seals stains made by smoke, mold, water, fire, ink, and dirt. Can be used on interior or exterior surfaces. Seals bleeding stains from wood and eliminates stains under wallcoverings.

Suggested Uses:

Plaster
Drywall
Concrete
Stone
Tile
Laminates

Packaging:

UPC Code	043281001793
Cans per case	12
Shipping weight per case	13.5 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.2

Properties:

Flammability	"Extremely Flammable"
Flash point	-4F
Specific Gravity	0.81
Solids Content	43%
VOC content	~55%, cannot exceed 60%
MIR value	~1.02, cannot exceed 1.20
HAPs content	~15%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Gasoline Resistance	No
Heat Resistance	250° F
Resin System	Polystyrene

Dry Time*:

To touch	10 minutes
To recoat	2 hours

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60° gloss meter