

Project:		Type:
,		-
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

WPS GEN 4 CLASSIC WALL PACK

ORDERING INFORMATION

Order code:

Model number: WPS-NS80-W/40K UPC: 069549016767 **DLC unique ID:** PLVXL8T0P2UF

Case quantity:

PHYSICAL DATA

Dimensions: 14.37" x 9.33" x 7.36" (365 mm x 237 mm x 187 mm)

Housing material: Aluminium die-cast

Lens Material: Prismatic tempered glass lens

PERFORMANCE DATA

Watts (W): 80 Volts (VAC): 120 - 277 Colour temperature (K)1: 4 000 Lumen output (Im)2: 11 242 Efficiency (Im/W): 146 CRI: >80 Finish: Bronze Photocell: No Dimming (Yes/No): Yes LED current (mA) 645 Power factor: 0.90 THD (%):

Operating temp. range: -40°C to 50°C

COMPATIBLE ACCESSORIES

Order code	Description	
68370	18" Bronze metal backplate	
68371	Bronze glareshield	
68372	Stainless Steel wireguard	

















dimmable
















Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.


This lighting equipment complies with Canadian standard ICES-005 for use in residential applications. Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.



 $^{^1}$ Typical colour temperature range: +/- 5 % 2 Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



DIMENSIONS



Qty	Description	Price
Name:	ations of the luminaire configuration mentioned above.	
Company: Signature:		
Signature:		Date:

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

