

Project:		Type:
,		31
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

WPA-L

LED ALL PURPOSE WALL PACK

Selectable color temperature (3 000/4 000/5 000 K) Integrated photocell

ORDERING INFORMATION

Order code:

Model number: WPA-LS1B-W-3C-BR-P 69549018730

Case quantity:

DLC unique ID: PLLA75MM6AAEC

PHYSICAL DATA

Dimensions: 10.96" x 6.58" x 5.2" (278.5 mm x 174.2 mm x 132.1 mm)

Lens material: Frosted polycarbonate lens

Housing material: Aluminum

PERFORMANCE DATA

Watts (W): 20 Volts (V): 120-277 Color temperature (K)1: 3 000/4 000/5 000 Lumen output (Im)2: 2 260 - 2 451 Efficiency (Im/W): 113 - 123 CRI: 70

Photocell (Yes/No): Yes Dimming (Yes/No): Yes Power factor: ≥0.9 THD (%): ≤20 Frequency (Hz): 50/60 Surge protection (kV): 2 Operating temp. range (°C): -40 to 40













fixture

((•)) ICES

005



fixture

















Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC Qualified Products List at www.designlights.org/search.

 $^{^1}$ Typical color temperature range: +/- 5 % 2 Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %



DIMENSIONS






PHOTOMETRIC DATA¹

68722 • WPA-LS1B-W-3C-BR-P-40K • 2 260.0 lm

Polar candela distribution



¹ Complete IES files available on our website.

Zonal lumen summary

Zone	Lumens	% Fixture
0-30	557.1	24.7%
0-40	894.6	39.6%
0-60	1 614.7	71.4%
60-90	549.7	24.3%
70-100	283.2	12.5%
90-120	57.8	2.6%
0-90	2 164.4	95.8%
90-180	95.7	4.2%
0-180	2 260.0	100%

Illuminance at a distance

Center beam fc			Beam	Beam width	
17'	2.99 fc	A	26.3'	23.9'	
34'	0.75 fc		52.7'	47.8'	
51'	0.33 fc		79.0'	71.7'	
68'	0.19 fc		105.4'	95.6'	
85'	0.12 fc		131.7'	119.5'	
102'	0.08 fc		158.0'	143.3'	
	Vert. spread: Horiz. spread:	75.5° 70.2°			

Qty	Description		Price		
I accept the specifications of the luminaire configuration mentioned above.					
Name:					
Company:					

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

Signature:

Date: