

AIR CONDITIONER 25,000 BTU WINDOW AC WITH ELECTRIC HEATER



450 18' x 25' 550 22' x 25' w 700 25' x 28' 31.25' x 32 1.000 1.500 37.5' x 40' CALCULATE ROOM SIZE 2,000 40' x 50' room length x room width = sq. ft. 3 CONFIRM WINDOW OPENING SIZE CHECK ELECTRICAL REQUIREMENTS Δ AX. HEIGHT (in.) 20A-230 MEASURE WINDOW OPENING IN INCHES for thru-the-wall units, confirm & measure wall opening size in inches DETERMINE IF YOUR CIRCUIT IS ADEQUATE

OUTLET CONFIGURATIONS

10,000

12,000

15,000

18.000

25,000

28,500

WINDOW AC FEATURES

- · Electronic controls
- Full range air direction control
- · Temperature output range of 62°F-86°F (17°C-30°C)
- · Auto, Sleep, Dry & Energy Saver modes
- · Full function remote control
- · 24 hour timer
- Window mounting kit · Auto restart function
 - 3PACH25000
- · Tilt-out filter access

Tilt-out filter access	w/ electric heater
UPC CODE	8-42149-02427-7
COOLING CAPACITY (BTU)	25,000/24,700
HEATING CAPACITY (BTU)	16,000
COVERAGE (sq. ft.)	1,400–1,500
EER	9.4
ENERGY STAR RATED	No
FAN SPEEDS (Cool/Fan/Heat)	3/3/1
AMPS (Cool)	11.3/12.4
AMPS (Heat)	22
WATTS (Cool)	2,660/2,628
WATTS (Heat)	4,800
DECIBELS (Hi/Mi/Lo)	63/61/58
WINDOW WIDTH (Min./Max.) (in.)	31/42
WINDOW HEIGHT (Min.) (in.)	191/2
UNIT DIMENSIONS (WxHxD) (in.)	26 ^{1/2} x 18 ^{3/4} x 26 ^{3/4}
PKG. DIMENSIONS (WxHxD) (in.)	31 ^{1/2} x 20 ^{1/2} x 29 ^{3/4}
STUFFING QTY. (20'/40'/40' HQ)	84/184/225
WEIGHT (Net/Gross) (lbs.)	137/153
REFRIGERATION	R410A
OUTLET CONFIGURATION	30 AMP 230V



PA/SS_3PACH25000/05022019

www.perfectaire.us support@perfectaire.us

5401 Dansher Road Countryside, IL 60525 (a) 866.996.9255 **(A) 630.323.2301**