

## Specifications

ARM5884



# Insulated A6 Nitrile Dipped Glove



## Product Features

- Sandy Nitrile Palm Coating
- 13 Gauge HPPE Outer Liner
- 10 Gauge Acrylic Inner Liner
- ANSI A6 Cut Level
- ANSI Impact Level 2
- Reinforced Thumb
- Contact Cold Protection
- Liner: High-Performance Polyethylene (HPPE) + Acrylic
- Coating: Nitrile
- TPR: Thermo Plastic Rubber
- Cuff: HPPE, Acrylic and Latex Elastic



## SPECIFICATIONS

SKU	Size
ARM5884S	7
ARM5884M	8
ARM5884L	9
ARM5884XL	10
ARM5884XXL	11

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

## Packaging

- 1 Pair on Hangtag
- 6 Pairs in Polybag
- 60 Pairs in Case

## Testing Performance

### ANSI/ISEA 105

Cut	1	2	3	4	5	6	7	8	9
Abrasion	1	2	3	4	5	6			
Puncture	1	2	3	4	5				

### ANSI/ISEA 138

Impact	1	2	3
--------	---	---	---

### EN388

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

### EN511:2006 – X2X

Convective Cold	1	2	3	4	X
Contact Cold	1	2	3	4	X
Water Penetration	0	1	X		