



1/6 hp utility pump, 115 V, 10' cord, automatic operation, standard level diaphragm switch

Item: 505715

Model: 5-ASP

Ratings

Frequency	60 Hz
Phase	Single-Phase
Amps - Full Load	2 A
Amps - Starting	3.5 A
Full Load Watts	220 W
Volts	115 VAC
Cord Length	10 ft
Lead Length	10 ft
Motor Type	Submersible
Continuous Duty	Yes
Thermal Overload Protection	Yes
Protection [IP]	IP68
Maximum Flow Rate - 60Hz	25 gpm / 1500 gph
Minimum Flow Rate - 60Hz	4.17 gpm / 250 gph
Shut-Off	26 ft
Minimum Head - 60Hz	1.31 ft
Shut Off Height - 60Hz	26.3 ft
Stages	1
Max Solid Handling Size	0.13 "
Control Type	Automatic

Liquid

Max Fluid Temperature	120 °F
-----------------------	--------

Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Aluminum
Pump Volute Material	Nylon
Impeller Type	Semi-open
Impeller Material	Nylon
Motor Shaft End - Material	Stainless Steel
Intake Screen Material	Nylon
Top Bearing Type	Sleeve
Bottom Bearing Type	Sleeve Bearing
Seal Material	Viton Retainer
Seal Type	Viton

Installation

Discharge Thread	FNPT
Discharge Type	Threaded - FNPT
Discharge	1 "
Product Length	7.5 "
Product Width	4.13 "
Product Height	7.78 "
Pump Length	7.8 "
Product Weight	8.7 lb
Product Weight w/ Pack	7.93 lb
Carton Length	9.45 "
Carton Width	6.3 "
Carton Height	9.45 "
Off Level - Range	1" - 4"
On Level - Range	6" - 9"

Other

Accessories Included	3/4" GHT garden hose adapter
Electrical Agency Approvals	UL
Standard Warranty	12 Months
	Warranty Terms and Conditions Link