



1/6 hp utility pump, 115 V, 25’ cord, manual operation

Item:	505712
Model:	Next Gen 5-MSP 25-Ft Cord

atings

Frequency	60 Hz
Phase	Single-Phase
Amps - Full Load	2 A
Amps - Starting	3.5 A
Full Load Watts	220 W
Volts	115 VAC
Cord Length	25 ft
Lead Length	25 ft
Motor Type	Submersible
Continuous Duty	Yes
Thermal Overload Protection	Yes
Protection [IP]	IP68
Maximum Flow Rate - 60Hz	25 gpm / 1500 gph
Minimum Flow Rate - 60Hz	4.17 gpm / 250 gph
Shut-Off	26 ft
Minimum Head - 60Hz	1.31 ft
Shut Off Height - 60Hz	26.3 ft
Stages	1
Max Solid Handling Size	0.13 "
Switch Type	Manual
Motor Cooling	Water

Liquid

Max Fluid Temperature	120 °F
-----------------------	--------

Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Aluminum
Pump Volute Material	Nylon
Impeller Type	Semi-open
Impeller Material	Nylon
Motor Shaft End - Material	Stainless Steel
Intake Screen Material	Nylon
Top Bearing Type	Sleeve
Bottom Bearing Type	Sleeve Bearing
Seal Material	Viton Retainer
Seal Type	Viton

Installation

Discharge Thread	FNPT
Discharge Type	Threaded - FNPT
Discharge	1 "
Product Length	6.1 "
Product Width	4.29 "
Product Height	8.07 "
Pump Length	6.1 "
Product Weight	7.75 lb
Product Weight w/ Pack	8.25 lb
Carton Length	7.28 "
Carton Width	6.3 "
Carton Height	9.45 "

Other

Accessories Included	3/4" GHT garden hose adapter
Electrical Agency Approvals	UL
Standard Warranty	12 Months
	Warranty Terms and Conditions Link