



SILICONE TOOLING FOAM

MASTERS® SILICONE TOOLING FOAM is designed to provide professional tooling results with no tools and less mess.

Once sprayed over freshly laid silicone, **MASTERS® SILICONE TOOLING FOAM** stops the silicone from spreading out over the surface. As you tool the silicone, the spray causes excess silicone to collect on your finger in a non-tacky ball that can easily be wiped off with a paper towel.

Directions:

- Lay new bead of silicone on surface.
- Spray **MASTERS® SILICONE TOOLING FOAM** along freshly laid silicone bead.
- Tool the silicone into place with finger.
- Wipe excess silicone away from finger; residual foam will evaporate.



Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
MSTF-170	MASTERS® Silicone Tooling Foam 170g	12	7 lbs	3.2 kg

Recommended for use with **MASTERS® SILICONE SEALANT**.



Find us on    

©2023 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on www.oatey.ca.