



DEHUMIDIFIER

FLAT PANEL | 22-PINT | 35-PINT | 50-PINT



3PFD22



3PFD35-2
3PFD50



**3-WAY
DRAINAGE**
BUCKET | PUMP | GRAVITY

	3PFD22	3PFD35-2	3PFD50	3PFD50
UPC	842149000486	842149001667	842149000509	842149000516
CAPACITY (pts./day)	22	35	50	50
COVERAGE (sq. ft.)	1,500	3,000	4,500	4,500
PUMP	—	—	—	✓
EEV	1.7	1.9	1.9	1.9
FAN SPEEDS	2	2	2	2
AMPS	2.2	3.25	4.8	4.8
WATTS	250	360	515	515
DECIBELS (Hi/Lo)	52/46.5	50/48	51/49	51/49
BUCKET CAPACITY (pts.)	6.3	12.7	12.7	12.7
UNIT DIMENSIONS (WxHxD) (in.)	15.5 x 19.75 x 10.25	15.5 x 19.75 x 10.25	15.5 x 24.25 x 11	15.5 x 24.25 x 11
PKG. DIMENSIONS (WxHxD) (in.)	16.5 x 20.5 x 11.5	16.5 x 20 x 11.5	17 x 26 x 13	17 x 26 x 13
CONTAINER QTY (20'/40'/40' HQ)	432/880/1100	432/880/1100	288/582/775	288/582/775
WEIGHT (Net/Gross) (lbs.)	32.5/34.5	40.5/43.75	41.25/44.5	42.25/45.25
MIN. OPERATING TEMP	41°F	41°F	41°F	41°F
REFRIGERANT	R32	R32	R32	R32
OUTLET CONFIGURATION	 15A-115V	 15A-115V	 15A-115V	 15A-115V

FEATURES

- Continuous drainage
- Adjustable digital humidistat provides precise humidity control
- Automatic defrost prevents evaporator from freezing
- Automatic shut off when bucket is full
- Comfort mode controls humidity based on room temperature
- Soft-touch electronic control panel
- Low temperature operation (down to 41°F)
- 24-hour programmable timer
- Ultra-quiet operation
- Easy roll casters
- Bucket full indicator
- Reusable filter
- Pump function ejects water to a sink or window, up to 16 vertical feet - perfect for areas where a floor drain is unavailable. (3PFD50)

