

ORDERING INFORMATION

Order code: 69321
Description: F14T5/35K/8/PS/G5/STD S2
UPC: 069549026315
Case quantity: 25

PERFORMANCE DATA


Shape: T5
Base: G5 (Min Bipin)
Starting method: Program Start (PS)
Wattage (W): 14
Colour temperature (K): 3 500
CRI: 85
Rated life on PS/PRS¹ ballast:
 Based on a 3 hour start 25 000
 Based on a 12 hour start 30 000
Initial lumens (lm): 1 350
Mean lumens (lm): 1 280
Nominal efficiency (lm/W): 96
TCLP compliant: Yes
Phosphor composition: Triphosphor
Nominal lamp operating frequency (Hz): 60
² **Minimum starting temperature (°C):** -10

¹ The life rating indicated is based on 3 hour burning cycles under specified conditions and with ballast meeting ANSI specifications.
² The minimum starting temperature is a function of the ballast.




Nominal length : 22 in (559 mm)
 Dia. : 5/8 in. (16 mm)

DIMENSIONS



SPECTRAL DISTRIBUTION



E Means this bulb meets federal minimum efficiency standards.

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

REV 26/10/2022

STANDARD